Directory Series S550 Tower Directory

- ▶ Free standing, double-sided tower directory
- ▶ No interior illumination necessary
- ▶ Steel free standing black base
- Digitally printed panel sits underneath a clear, non-glare cover
- ▶ Satin aluminum or black extrusions available

Standard Sizes

▶ 79" x 23 ¹/₂"

Additional Information

- ▶ Directories available in virtually any color
- ► Logos available; digital file required (eps, dmx, ai and wmf files accepted)







S550 Tower Directory Sign Suggested Specifications

PART 1 - GENERAL

1.01 SUMMARY

A. Interior non-illuminated directory signage 1.02 SECTION INCLUDES

A. S550 Doubled Sided Tower Directory

1.03 REFERENCES

- A. Americans with Disabilities Act (ADA)
- B. American National Standards Institute (ANSI)

1.04 SYSTEM DESCRIPTION A Performance Requirements: Provide

- A. Performance Requirements: Provide signage systems that conform to the following requirements of regulatory agencies and the quality control of InPro SignScape.
- Signage shall comply with all applicable provisions of the ADA and ANSI A117.1-1998

1.05 SUBMITTALS

- A. Product Data: Manufacturer's printed product data for each signage system indicated in this section.
- B. Manufacturer's Installation Instructions: Printed Installation Instructions for each signage system.

1.06 DELIVERY, STORAGE, AND HANDLING

- A. Deliver materials in unopened factory packaging to the jobsite.
- B. Inspect materials at delivery to assure that specified product have been received.
- C. Store in original packaging in a climate controlled environment away from direct sunlight.

1.07 WARRANTY

A. Standard InPro SignScape limited lifetime warranty against material and manufacturing defects.

PART 2 - PRODUCTS

2.01 MANUFACTURERS

- A. Acceptable Manufacturer/Distributor: InPro SignScape,InPro Corporation PO Box 406, Muskego, WI 53150 USA, Telephone 800-222-5556, Fax: 888-715-8407
 - E-mail: service@inprocorp.com
- B. Substitutions: Not permitted
- C. Provide all signage systems from a single manufacturer.

2 02 MATERIALS

- A. Signage Panel: Provide printed graphics panel on 80 pound paper digitally printed with UV cured ink. Size 78.875 (2.003m) x 23.52" (.597m)
- B. Signage Panel Cover: Provide .075"thick Polycarbonate Signage Panel Cover. One side shall be non-glare, the other side shall be glossy.
- C. Frame: Provide extruded aluminum sign frame. Color shall be black anodized, brushed silver or gold.
- D. End Cap: Provide end cap with matching screws to finish top of directory tower. Color shall be black anodized, brushed silver or gold
- E. Steel Base: Provide oval shaped painted steel base plate. Color shall be black paint.

2.03 DOUBLE SIDED DIRECTORY

- A. Double Sided Directory
- 1. Style/Size:
- a. S550 Slim, Free Standing, width is 23.62" (600 mm).
 height 79.375" (2.016m).
- Printed Graphic Size: 23.52" (600 mm). 78.875" (2.003m).

PART 3 EXECUTION

3.01 EXAMINATION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.

3.02 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.03 INSTALLATION

- A. Install in accordance with manufacturer's instructions.
- B. Locate signs in accordance with approved shop drawings and ADA requirements.
- C. Install signs after surfaces to receive signage are finished.

3.04 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.



