



PolyVision PJ920 ultra-short throw projector for ēno® one


PJ920 specifications

(PJ905 short throw projector is also available. See separate specifications.)


- DLP with Brilliant Color technology
- Native resolution: WXGA (1280 x 800)
- Aspect ratio: 16:10 Native, 4:3
- Brightness: 2500 Lumens (typical); 2200 Lumens (eco mode)
- Lamp life: 4000/6000 hrs.
- 6-segment color wheel (RGBCWY)
- Contrast ratio: 1500:1
- Throw Ratio: 0.192
- Keystone correction: ±15°
- 10 watt built-in speaker
- 3D-ready
- I/O connections: VGA (x2), HDMI, S-Video, Composite Video RCA, Audio mini jack (in and out loop), VGA Monitor Out
- Control terminals: LAN Ethernet RJ45, USB, Serial RS-232
- Networks: IP for remote management
- Compatibility for video system: NTSC/NTSC 4.43, PAL-B/G/H/I, SECAM
- Compatibility for video interface: Composite, S-Video, Component YPbPr, Component YCbCr, VESA Standard
- Format compatibility: QVGA, VGA, SVGA, XGA, SXGA+, UXGA
- Acoustic noise: 29dB (typical 230 W);
 27 dB (typical eco mode 190 W)


- Weight: <20 lbs. (<9 kg)
- · Lamp replacement accessible when mounted
- Warranty: 3 years on projector; 3 years on lamp
- Kensington theft protection
- Power cord: 4.5m
- VGA cable: 4.5m
- USB cable: 4.5m
- Power requirements: 100V-240V, 50 / 60 Hz
- Power consumption: 290 W (normal use); 240 W (eco mode);
 V (standby)
- Temperature: 5°C ~ 40°C; -10°C ~ 60°C (non-operating)
- Operating altitude: sea level to 10,000' at 23°C
- Humidity: 10% 85% (no condensation);
 5% 95% (no condensation, non-operating)

Choose the PolyVision PJ920 ultra-short throw projector for optimal image projection with the ēno one projection solution.



ēno one height-adjustable mobile configuration








SKU	Interactive whiteboard	Projector	Mount
ēno one 2610 MOB UST	ēno 2610	PJ920	Height-adjustable carriage + Mobile Leg Kit
ēno one 2810 MOB UST	ēno 2810	PJ920	Height-adjustable carriage + Mobile Leg Kit


ēno one height-adjustable wall mount configuration





SKU	Interactive whiteboard	Projector	Mount
ēno one 2610 AWM UST	ēno 2610	PJ920	Height-adjustable carriage
ēno one 2810 AWM UST	ēno 2810	PJ920	Height-adjustable carriage

ēno one fixed wall arm configuration





SKU	Interactive whiteboard	Projector	Mount
ēno one 2610 FWA UST	ēno classic 2610	PJ920	Fixed wall arm
ēno one 2810 FWA UST	ēno classic 2810	PJ920	Fixed wall arm
ēno one 2650 FWA UST	ēno click 2650	PJ920	Fixed wall arm
ēno one 2850 FWA UST	ēno click 2850	PJ920	Fixed wall arm

eVision™ PolyVision is committed to move toward sustainability in all areas of environmental stewardship—to protect people, replenish natural resources, and restore the communities in which we work and live.

©2011 PolyVision Corporation. All rights reserved. Trademarks used herein are the property of PolyVision Corporation or of their respective owners. PolyVision Corporation reserves the right to make changes in product design, construction or detail, and to discontinue any product or material without notice.

