

Corridor
Walkways
Accent
General Lighting



Specifications



Certifications The fixture shall be ETL and CETL listed for wet location and concrete pour. Also listed for wire through. The fixture shall meet ADA requirements.

Lamp/Ballast Housing Cast aluminum with a minimum wall thickness of 3/16" and two 3/4" NPT conduit entrances for through-wiring capability.

Face Plate Cast aluminum standard with cast bronze optional. Secured to lamp/ballast housing with four 5/16" stainless steel allen cap screws. Gasketed to prevent entrance of dust, insects and moisture.

Lens Tempered clear glass sealed to face plate with silicone.

Lampholder Porcelain 4KV pulse rated medium base, for HID and Incandescent lamp source.

Reflector Highly polished specular aluminum multifaceted for optimum efficiency.

Finish BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

PROJECT
FIXTURE TYPE
CATALOG#

2930 South Fairview Street
 Santa Ana, CA 92704
 Phone: 714 668 3660
 Fax: 714 668 1107
 allighting@earthlink.net
 http://www.allighting.com

SP-28

Product Order Guide

Series	Max Watts	Lamp Type	Voltage ¹	Finish ¹	Options
SP-28	100 MH	E17	120	BK Black	QS Quartz Standby
	100 HPS	E17	208	BZ Bronze	EMG Emergency Battery Backup
	42 CFT	CFT ²	240	WH White	
	13 CF	CF ²	277	GR Green	
	26 CFQ	CFQ ²		NA Natural Aluminum	
				GY Gray	
				CC Custom Color	

1 Consult factory for other colors and voltages
 2 CF = single biax, CFQ = double biax, CFT = triple biax

Example: SP-28-100MH-E17-120-BK

Luminaire Dimensions

Luminaire	A	B
SP-28	14"	6-1/2"

