

- Building Entrances**
- Landscape Accent**
- Walkways**
- Planted Areas**
- Parks**
- Parking Lots**



LL-105



LL-106



LL-107

**METRIC**

### Specifications

ETL cETL IP65

- Certifications** The fixture shall be ETL and CETL listed for wet location and have a protection rating of IP65, dust-tight and jet-water proof.
- Housing** The housing shall be constructed of die cast aluminum. The housing mounting post shall be of extruded aluminum and cast aluminum base plate.
- Ballast** The ballast shall be readily accessible, removable and insulated. The fixture is to be pre-wired and electronically tested before shipment.
- Lens** The lens shall be prismatic frosted glass or opal polycarbonate (LL-105 and LL-106). The lens shall be clear glass (LL-107).
- Hardware** All exposed hardware shall be stainless steel.
- Mounting** The fixture shall be mounted with four socket cap screws on a cast aluminum base.
- Finish** BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

<b>PROJECT</b>
<b>FIXTURE TYPE</b>
<b>CATALOG#</b>

2930 South Fairview Street  
 Santa Ana, CA 92704  
 Phone: 714 668 3660  
 Fax: 714 668 1107  
 allighting@earthlink.net  
 http://www.allighting.com

# LL-105/106/107

## Product Order Guide

Series	Max Watts	Lamp Type	Voltage <sup>1</sup>	Overall Height	Finish <sup>1</sup>	Options
LL-105	60 Halogen <sup>3</sup>	BT15	120	30" 762 mm	BK Black	GL Prismatic Frosted Lens
LL-106	60 INC	T10	208	36" 914 mm	BZ Bronze	PL Polycarbonate Lens
	13 CF	CF <sup>2</sup>	240	42" 1066 mm	WH White	S Single lamp housing
	2(13) CF	CF <sup>2</sup>	277		GR Green	D Double lamp housing
	26 CFQ	CFQ <sup>2</sup>			NA Natural Aluminum	
	42 CFT	CFT <sup>2</sup>			GY Gray	
					CC Custom Color	
LL-107	75 Halogen	T3mini				S Single lamp housing
	13 CF	CF <sup>2</sup>				D Double lamp housing
	26 CFQ	CFQ <sup>2</sup>				
	26 CFT	CFT <sup>2</sup>				




1 Consult factory for other colors and voltages

2 CF = single biax, CFQ = double biax, CFT = triple biax

3 GL option only

## Example: LL-105-13CF-120-42-BK-PL-D

## Photometric Data



LL-105-(2)13CF-GL-S

1,720 Lumens

3.0 ft Mounting Height

ISOLUX Curves - value in initial footcandles

LL-106-60INC-GL-S

890 Lumens

3.0 ft Mounting Height

ISOLUX Curves - value in initial footcandles

LL-107-13CF-BK-S


860 Lumens

3.0 ft Mounting Height


ISOLUX Curves - value in initial footcandles

## Luminaire Dimensions


Luminaire	A		B		C		D		E		Weight	
	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	lbs.	kg
LL-105	5.50	140	7.87	200	42.00	1066	11.50	292	9.45	240	43.0	19.5
LL-106	5.90	150	8.66	220	42.00	1066	11.50	292	9.45	240	43.0	19.5
LL-107	6.10	155	9.06	230	42.00	1066	11.50	292	9.45	240	41.9	19.0



LL-105



LL-106



LL-107