

Walkways
Building Entrances
Parking Lots
Shopping Malls



Specifications



Certifications The fixture shall be ETL and CETL listed for wet location.

Description The luminaire shall be cast aluminum construction, with a floral pattern, a globe holder with integral enclosed ballast housing, and a decorative one piece globe with an 8" neck. The luminaire base shall measure 10-1/4" in height and 4-3/4" diameter at the bottom.

Materials The luminaire base and ballast housing shall be heavy wall cast aluminum formed true to the pattern with complete detail. Globe material shall be clear (standard) or white, textured polycarbonate. All hardware shall be stainless steel. All exterior hardware shall be tamper resistant.

Installation The luminaire shall mount on a 3" O.D. tenon with six 1/4" dia. socket set screws. The globe shall be secured to the luminaire by four 1/4" dia. socket set screws. The ballast and socket assembly shall be furnished with a quick disconnect plug and mount on a removable ballast plate. The ballast plate shall be removed by loosening two screws. A strain relief shall be provided in the luminaire below the quick disconnect plug to hold post wires in place.

Finish BK-BZ-WH-GR-GY-NA baked enamel standard, other colors available.

Light Source Luminaires shall be furnished with either an H.I.D. ballast and socket assembly or an incandescent socket. Sockets shall be glazed porcelain mogul or medium base, with a copper alloy nickel plated screw shell and center contact. Ballast shall be core and coil, high power factor, regulating type.

| |
|---------------------|
| PROJECT |
| FIXTURE TYPE |
| CATALOG# |

2930 South Fairview Street
 Santa Ana, CA 92704
 Phone: 714 668 3660
 Fax: 714 668 1107
 allighting@earthlink.net
 http://www.allighting.com

AA-08

Product Order Guide

| Series | Max Watts | Lamp Type | Voltage ¹ | Optics | Finish ¹ | Options |
|--------|-----------|-------------------|----------------------|--------|---------------------|--------------------------|
| AA-08 | 175 MH | E-17 ² | 120 | CLF5 | BZ Bronze | HSS House Side Shield |
| | 250 MH | ED-28 | 208 | CLF3 | BK Black | PCB Button Photo Control |
| | 175 HPS | E-17 ² | 240 | | GR Green | F Fusing |
| | 250 HPS | ED-18 | 277 | | WH White | FF Double Fusing |
| | | | | | NA Natural Aluminum | |
| | | | | | GY Gray | |
| | | | | | CC Custom Color | |

1 Consult factory for other colors and voltages
 2 Lamps 175 W and below are medium base.

Example: AA-08-100MH-E17-120-CLF5-GR

Optics

| | |
|------|------------------|
| CLF5 | Type 5 Refractor |
| CLF3 | Type 3 Refractor |

Luminaire Dimensions

| Luminaire | A | B | Weight | EPA |
|-----------|-----|-----|--------|------|
| AA-08 | 15" | 35" | 20# | 1.35 |

