

CACHET:

Style Code

6TCHT

Specifications

Construction	Textured Loop Pattern
Yarn Content	Avalar® RE Nylon
Odor Reduction	Puralax®
Dye Method	Solution Dyed
Machine Gauge	1/10 in (39.4 in./10 cm.)
Stitch Count	10 S.P.I (39.4/ 10 cm.)
Finished Pile Thickness	.088 in. (2.24 mm.)
Average Density	6,545
Yarn Weight Tufted	16 oz. /yd. ² (610 g./m. ²)
Primary Backing	Non Woven
Secondary Backing	Nexterra®
Total Recycled Content	40% minimum post consumer recycled content based on total weight of product
Modular Tile Width	24" x 24" (61 cm. x 61cm.)

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
CRI Green Label Plus	Certification #GLP8595

Warranties

Wear	Lifetime Limited Warranty
Static	Lifetime Warranty
Edge Ravel	Lifetime Warranty
Delamination	Lifetime Warranty, under normal use
Tuft Bind	Lifetime Warranty
Stain	Lifetime Limited Warranty

Additional Information

Custom Colors	iDESIGN CARPET.COM
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B Ō L Y Ü

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075