

SASHAY:

Style Code

SAS

Specifications

Construction	Tip-Sheared Textured Loop
Yarn Content	Zeftron® Nylon with 25% recycled content
Dye Method	Solution/Space
Machine Gauge	1/8 in. (31.5 col./10 cm.)
Stitch Count	13 S.P.I. (57.4/10 cm.)
Finished Pile Thickness	.163 in. (4.14 mm.)
Average Density	6,405
Yarn Weight Tufted	30 oz./yd.2 (1288 g./m2)
Primary Backing	Masterline® Woven Primary
Secondary Backing	Woven Polypropylene
Width	12 feet (3.66m.)
Pattern Repeat	.40" w x 2.8" l (15.2 cm. x 7.1 cm.)

Performance

Static Control	Less Than 3.5 k.v. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1(ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
CRI Green Label Plus	Certification #GLP7078

Warranties

Zeftron® Stain Warranty	Lifetime Stain Removal – Limited Guarantee
Zeftstat® Warranty	Lifetime Carpet Static Warranty
Zeftwear® Warranty	Lifetime Carpet Wear – Limited Warranty
Zeftron® Certification	Class III, Extra Heavy Traffic
enviro6ix®	Minimum of 25% recycled content
Zeftron® Recycling	6ix Again®

Additional Information

Custom Colors	Contact Sales Representative
Backing Options	See iLoc® backings at www.bolyu.com
Samples	800 451 1250

Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances. Components may be changed without notice due to raw material shortages and/or technological advances. Such variances do not affect performance.



B O L Y U

201 Princeton Boulevard
Adairsville, Georgia 30103
800 451 1250

335 Roxton Street
Acton Vale, Quebec
Canada J0H 1A0
888 467 5075