

LEDIA LF ID

LEDIA LF ID model for interior recessed in-floor use features leveling adjustment allowing installation to be flush with floor surface. It is available in four sizes. Luminaire assembly may be adjusted for depths from 2.4" to 5.5". Remote 120vAC/10vDC power supply unit is required. LED colors; red, blue, green, amber, white. Contact factory for in-wall applications.



Listed 1838, Low Voltage Landscape Lighting Systems

Model	Dimensions	Qty LEDs	Wattage
LEDIA-LF-ID-04	3.7" x 3.7"	16 LEDs	2
LEDIA-LF-ID-08	7.7" x 7.7"	48 LEDs	6
LEDIA-LF-ID-12	11.6" x 11.6"	64 LEDs	8
LEDIA-LF-ID-16	15.6" x 15.6"	96 LEDs	12

Additional information:

Drawings

Downloads

[LF-ID-04.swf](#)

[LF-ID-08.swf](#)

[LF-ID-12.swf](#)

[LF-ID-16.swf](#)

Catalogue page

Downloads

[Hessamerica_LEDIA_LF.pdf](#)

Photometric reports

Downloads

[LEDIA_LF_100_1_LED.ies](#)

[LEDIA_LF_200_1_LED.ies](#)

[LEDIA_LF_300_1_LED.ies](#)

[LEDIA_LF_400_1_LED.ies](#)

Specification sheets

Downloads

[LEDIA LF ID 04 LED Illuminating Tile](#)

[LEDIA LF ID 08 LED Illuminating Tile](#)

[LEDIA LF ID 12 LED Illuminating Tile](#)

[LEDIA LF ID 16 LED Illuminating Tile](#)

Product brief

References

