



LEDIA LL OD LED Illuminating Strip for Exterior In-Ground Use

Elegant in any context, LEDIA LL is ideally suited to a variety of applications. It is available in four lengths. Frameless glass lens integrates subtly into pavers or concrete walkways to highlight or act as directional identifiers. The tempered glass lens, coated internally with a translucent white coating, is bonded to the stainless steel housing providing a sealed enclosure. LEDIA mounts into a recessed stainless steel sub-

Dimensions

9.5" x 1.1"

18.1" x 1.1"

27.2" X 1.1"

35.8" x 1.1"

Model

LEDIA LL-OD-09

LEDIA LL-OD-18

LEDIA LL-OD-27

LEDIA LL-OD-36

frame, which serves as a cable vault for making power connections. Remote 120vAC/10vDC power supply unit is required. LED colors; red, blue, green, amber, white. See technical sheet for details. Underwater model is available. See LEDIA LL UW catalog page for details.

(UL) Listed 1838, Low Voltage Landscape Lighting Systems

Qty LEDs

16 LEDs

32 LEDs

48 LEDs

64 LEDs

use features leveling adjustment allowing installation to be flush

with floor surface. It is available in four lengths. Luminaire assembly may be adjusted for depths from 2.4" to 5.5". Remote 120vAC/10vDC power supply unit is required. LED colors; red, blue, green, amber, white. See technical sheet for details. Underwater model is available. See LEDIA LL UW catalog page for details.

LEDIA LL ID

LED Illuminating Strip

for Interior In-Floor Use

LEDIA LL ID model for interior

(L) Listed 2108, Low Voltage Lighting Systems

Wattage	Model	Dimensions	Qty LEDs	Wattage
2	LEDIA LL-ID-09	9.5" X 1.1"	16 LEDs	2
4	LEDIA LL-ID-18	18.1" x 1.1"	32 LEDs	4
6	LEDIA LL-ID-27	27.2" X 1.1"	48 LEDs	6
8	LEDIA LL-ID-36	35.8" x 1.1"	64 LEDs	8



3.174