Slate 2017

Open House 2334

Specifications

Contents
35% post-consumer recycled polyester
65% pre-consumer recycled polyester

Weight
12.4 ± 1.0 oz./lin. yd.

Width
54" min. useable

Cleaning Code

Standard Care Label W-S. Clean with water based cleaning agents, foam or pure, water free solvents. Vacuuming or light brushing is recommended to prevent dust and soil buildup.

Performance

Breaking Strength (ASTM D5034)
275 lbf min. warp and fill

Tear (ASTM D2261)
35 lbf min. warp and fill

Seam Slippage (ASTM D4034)
50 lbf min. warp and fill

Pilling resistance (ASTM D3511)
Class 4 min.

Colorfastness to light (AATCC 16 Option 3)
Grade 4 min. at 40 hours

Colorfastness to crocking (AATCC 8)
Grade 4 min. dry & Grade 3 min. wet

Colorfastness to water (AATCC 107)
Class 3 min. for staining
Class 4 min. for color change

Wyzenbeek Abrasion resistance (ASTM D4157)
250,000 double rubs min. cotton duck

Flammability
CA Tech Bulletin 117 Sec. E
NFPA 260/UFAC Fabric Classification - Class I



Terratex is a registered trademark of True Textiles, Inc. and designates fabrics that are made from 100% recycled or compostable material using increasingly sustainable manufacturing practices to produce a high quality product that is recyclable at the end of its useful life. (terratex.com)

CO^2 emissions from 100% of the electricity used by the manufacturer to produce this product have been measured and offset in accordance with the CarbonNeutral Protocol.

Guilford of Maine