

Bruno® Wall

Partial Perf T8

Type:

Project:

SPECIFICATIONS

Wall Mount — Modular / 8" X 2" Rectangular

BRW7


CATALOG NUMBER

FT


Examples: BRW7 2 32 WHR 40FT R8 GEB10 DCT LP835 SCEP – BRW7 2 32 WHR 32FT R8 277 GEB10 1SE EL DCT LP835

AVAILABLE FIXTURES

BRW7 - 1



BRW7 - 2



SPECIFICATIONS

Construction

Housing is a nominal 8 1/4" x 1 11/16" rectangular channel formed from cold-rolled steel. 5/8" thick aluminum die cast end cap is standard, 4" sculpted die cast aluminum end cap is optional.

Reflectors

Die formed white painted reflector.

Shielding

Die-punched perforations on lower housing with acrylic opal diffuser overlay.

Finish

Fine textured white polyester powder paint standard. Consult factory for special finish requirements.

Electrical

Specify 120V, 277V, or 347V. Pre-wired with 16AWG fixture wire. For special circuiting or wire gauge, consult factory. Quick connect electrical connectors included. UL and C-UL listed and labeled.

Fixture Length

4' 1/6", 8' and 12' lengths in a single section. For total fixture length, add 5/8" for each flat end cap and 4" for each sculpted end cap. Using internal joiners, 4', 8' and 12' sections can be joined to form longer rows.

ORDERING LOGIC

Use guide below to order complete fixture runs from four feet to one-hundred feet in increments of four.

FT							
Fixture	# of Lamps in Cross Section	Lamp Type	Reflector	Nominal Row Length ¹	Maximum Section Length	Voltage	Ballast Type
BRW7	1 2	32 T8	WHR White Reflector			120 277 347	GEB <20% THD ELECTRONIC GEB10 <10% THD ELECTRONIC Dimming Ballasts Available: ADEZ ² Advance Mark 10 ECO10 ² Lutron ECO-10 ADZT ² Advance Mark 7 0-10V dimming Reference Ballast Chart on website or consult factory for other options.
# of Emergency Modules	Emergency Type ³	Switching	Lamp Color	Finish	Options		
Blank (None) 1SE 1 section 2SE 2 sections XSE X sections	Blank (None) EL ² Emergency Battery Pack EC Emergency / Night Light Circuit EN ² Emergency Battery Pack with Night Light Circuit	SCT Single Circuit DCT Dual Circuit	L/LP No Lamp LP830 3000K 80+ CRI LP835 3500K 80+ CRI LP841 4100K 80+ CRI LP730 3000K 70+ CRI LP735 3500K 70+ CRI LP741 4100K 70+ CRI Reference Lamp Chart on website or consult factory for other options.	C210 Standard White White (fine-textured low gloss) C110 Painted Aluminum Finish C099 Custom Color	DL Damp Location Label DU Dust Cover ELH EM Through wire w/ Separate Feed ELS EM Through Wire w/ Single Feed ELS2 Normal feed w/ EM Separate Neutral GLR Fusing (Fast blow) GMF Fusing (Slow Blow) NYC New York City Code SCEP Sculptured End Cap		

Notes:

- 1 Must be in 4' increments (consult factory for additional increments).
2 Not available in 347 volt.

- 3 Emergency type is installed in last 4' of fixture sections and are not available concurrently. Separate feed required unless ELS/ELH is specified.

Bruno® Wall

Partial Perf T8

Type:

Project:

PHOTOMETRICS

Wall Mount — Modular / 8" X 2" Rectangular

BRW7

1-LAMP T8

2-LAMP T8

