

SCEP option

10CRM4QS

specifications

CONSTRUCTION — Die formed cold-rolled steel housing. Flat steel end plate standard. Die-cast aluminum end cap optional.


SHIELDING — Parabolic semi-specular aluminum louvers (SSB), white painted steel baffle (SBL) or white painted perforated steel baffle (PPL). Optional Opal Diffuser (OPD) overlay.

REFLECTORS — Die-formed specular aluminum or pre-painted white steel.

FINISH — Fine textured white polyester powder paint.

FIXTURE LENGTH — 4', 8' and 12' individual fixture sections for nominal suspension spacing of 4', 8' and 12'. Add 1/8" for each standard end cap or 4" for each optional sculptured end cap to determine total fixture length. Using internal joiners, 4', 8' and 12' sections can be joined to form longer length fixtures.

dimensions / lamping



light distribution



See Typical Application section for sample layouts.

ordering logic

Sample Catalog Number: 10CRM4QS 2 32 WHR SSB 40FT R12 277 GEB10 DCT LP835 F1/18 C210 SCEP

Fixture	# of Lamps in Cross Section	Lamp Type	Reflector	Distribution	Shielding	Baffle	Fixture Row Length	Maximum Section Length	Voltage	Ballast Type	▶▶▶
10CRM4QS	1 2 3	28T5 28W T5 54T5HO 54W T5HO 32 T8	WHR White reflector SPR Specular reflector	(Blank) Standard 65/35 20/80 20% Up, 80% Down 40/60 40% Up, 60% Down 0/100 0% Up, 100% Down CLI¹ Center Lamp Isolator	(Blank) No opal overlay OPD Baffle w/ Opal overlay	SSB Semi Specular Baffle SBL White Blade Baffle PPL White Perforated Blade Baffle	X FT (4' increments)	R4 4' section(s) R8 8' section(s) R12 12' section(s)	120 277	GEB10 <10% THD Electronic (all lamp types) OS5C Osram 0-10V dim or line voltage control (32 T8) ADEZ Advance Mark 10 dim (54T5HO) OSDIM Osram 0-10V dim (54T5HO)	
▶▶ # of Emergency Modules	Emergency Type²	Switching	Lamp Color	Mounting Type /	Overall Suspension⁵	Finish	Options				
(Blank) None 1SE 1 section 2SE 2 sections XSE X sections	(Blank) None EC³ Emergency circuit EL Emergency battery pack EN³ Emergency battery pack w/night light circuit	SCT Single circuit DCT³ Dual circuit	L/LP* No lamp LP830 3000K 80+ CRI LP835 3500K 80+ CRI LP841 4100K 80+ CRI *Wired for full wattage lamps only, do not install low wattage lamps	F1/ T-bar ceiling (universal mounting bracket) F1A/ T-bar ceiling (UMB with integrated J-box) F2/ Hard ceiling (horizontal J-box)	12 12" 15 15" 18 18" 21 21" 24 24" XX XX" Overall suspension is measured from ceiling to bottom of fixture	C210 White white (fine-textured low gloss)	ACG Adjustable cable grippers CP Chicago plenum (available with F1A only) DU⁴⁶ Dust cover ELH Emergency through wiring w/separate feed ELS³ Emergency through wiring w/single feed, shared neutral ELS2³ Emergency through wiring w/single feed, separate neutrals GLR Fusing (fast blow) GMF Fusing (slow blow) MCS Matching feed canopy at support OBJ Offset junction box SCEP Sculptured end cap				

Notes: 1 Available with 3 lamp cross section only 2 Emergency type is installed in last 4' of fixture sections. Separate feed required unless ELS or ELS2 is specified 3 Not available with dimming 4 Not available with a distribution selection 5 Maximum of 240" 6 Not available with 3 lamp 54T5HO

PEERLESS®
An **Acuity Brands** Company

