




PEERLESS®
An **Acuity** Brands Company



There are so many diverse needs for affordable, high-quality illumination, we've given this lighting family multiple personalities just to keep up. Consider Cerra an equal opportunity lighting design platform.



Cerra has an answer for virtually every lighting requirement throughout offices, classrooms, libraries—just about everywhere people need quality light by which to work and study.


Its pure crescent architectural form is expressed in numerous variations, from simple to intricate, with all manner of available lampings, distributions, mountings and configurations. The lighting performance is, of course, peerless. So however you configure it, Cerra makes "lighting for people" a truly egalitarian proposition.

Cerra 7 and Cerra 10 indirect, indirect/open, perforated, Lightvent™ and indirect/direct luminaires are engineered to meet strict IES RP-1 standards for office lighting. High performance specular reflectors are available for critical applications. Advanced

HOT-5® technology optimizes T5HO lamping in Cerra 7; the larger-scale Cerra 10 offers a choice of T5, T5HO or T8 lamping.

Optional sculptured end caps present a more refined look to the luminaire when desired. Tenon connectors and corners expand the design possibilities with configurations. Effortless power connections and a universal mounting system provide ultimate flexibility and installation cost savings. The Cerra family's easy modularity provides flexibility to suit the dimensions and uses of a space.

Elegant wall-mounted Cerra complements Cerra 7 and Cerra 10 suspended systems, extending the distinctive look and delivering soft, even illumination onto perimeter surfaces.



Sculptured End Cap

Cerra 7 & 10

SPECIFICATIONS

CONSTRUCTION

Die-formed cold-rolled steel housing. Flat steel end plate standard.
Die-cast aluminum end cap optional.

SHIELDING

Die-punched square windows on 7CRM2 and 10CRM2. Perforated steel and steel baffles on 7CRM3 and 10CRM3. Parabolic semi-specular aluminum louvers (SSB), white painted parabolic louvers (WPB), white painted steel baffle (SBL) or white painted perforated steel baffle (PPL) on 10CRM4. Fully perforated steel housing on 10CRM6. Partially perforated steel housing on 7CRM7 and 10CRM7. Opal acrylic diffuser overlay optional on 10CRM4, standard on all other fixtures.

REFLECTORS

Die-formed specular aluminum or pre-painted white steel.


FINISH

Fine textured white polyester powder paint standard, custom colors available.

FIXTURE LENGTH

4', 8' and 12' individual fixture sections for nominal suspension spacing of 4', 8' and 12'. Add 1/16" for each standard end cap or 3" on Cerra 7 or 4" on Cerra 10 for each optional sculptured end cap to determine total fixture length. Using internal joiners, 4', 8' and 12' sections can be joined to form longer length fixtures.

OPTIONS



QUICKSHIP

Products shown with QuickShip icons are part of our express product selection. Go to www.peerless-lighting.com for details.




CONFIGURATIONS

Corner and tenon connectors available for suspended configurations. For inspiration see pages 198-199. Additional pattern connector details available at www.peerless-lighting.com.


ORDERING INFORMATION

DIMENSIONS / LAMPING




Cerra 7

(1, 2, 3) T5, T5HO




Cerra 10

10CRM1 (1, 2, 3, 4) T8
10CRM2 (2, 3, 4) T8
10CRM3 (1, 2, 3) T5, T5HO or (2, 3, 4) T8
10CRM4 (1, 2, 3) T5, T5HO or T8
10CRM6 (2) T8
10CRM7 (2, 3, 4) T8



PERFORMANCE



7CRM2 with SPR (2) T5HO

99.0% Indirect
1.0% Direct
83.5% Efficiency

For complete photometric data see specification sheets at www.peerless-lighting.com.

Fixture	# of Lamps in Cross Section	Lamp Type	Reflector (does not apply to 10CRM4)	VDR (10CRM4 only)	Shielding (10CRM4 only)	Nominal Row Length*	Maximum Section Length	Voltage	Ballast Type	# of Emergency Modules
7CRM1	1	54T5HO	WHR White Reflector (Standard)	(Blank) None	(Blank) None	_____ FT	R4 4'	120	GEB <20% THD Electronic (T8 only)	(Blank) None
7CRM2	2	28T5	SPR Specular Reflector (not available with 7CRM3 & 10CRM3)	CLI Center Lamp Isolator	OPD Opal Diffuser	*Must be in 4" increments.	R8 8'	277	GEB10 <10% THD Electronic Ballast	1SE 1 Section
7CRM3	3	32 (T8)					R12 12'	347	CCR* (2) 1.18BF/(1) .88BF	2SE 2 Sections
7CRM7	4	See Dimensions/Lamping section above for available # of lamps and lamp type per fixture.							OSPSX Osram .71BF (T8 only)	XSE X Sections
10CRM1									ECO10 ¹ Lutron ECO-10 dim	
10CRM2									ADZT ^{1,2} Advance Mark 7 0-10V dim	
10CRM3									*Only use with 10CRM4, 3 lamp, T8 and CLI option	
10CRM4									1 Not available in 347 Volt	
10CRM6									2 Not available with 28T5	
10CRM7									Reference ballast chart on web site or consult factory for other options.	



Sample Catalog Number: 7CRM1 2 54T5HO WHR 40FT R12 277 GEB10 DCT LP835 C210 SCEP F1/18

7CRM1/10CRM1 Cerra 7 or Cerra 10 Indirect**7CRM2/10CRM2** Cerra 7 or Cerra 10 Indirect/Open**7CRM3/10CRM3** Cerra 7 or Cerra 10 Lightvent**10CRM4** Cerra 10 Indirect/Direct**10CRM6** Cerra 10 Indirect/Full Perf**7CRM7* / 10CRM7** Cerra 10 Indirect/Partial Perf

*QuickShip available with 10CRM7 only

WALL MOUNT COMPANIONS



Emergency Type	Switching	Lamp Color	Finish	General Options	Mounting Type /	Overall Suspension	Mounting Options
(Blank) None	SCT Single Circuit	L/LP No lamp	(Blank) None	DL Damp Location Label	F1 T-Bar Ceiling (Universal Mounting Bracket)	12 12"	ACG Adjustable Cable Grippers
EL Emerg. Battery Pack	DCT Dual Circuit	LP830 3000K 80+ CRI	C210 Textured White White (low gloss)	DU Dust Cover	15 15"	18 18"	CP Chicago Plenum (F1A)
EC Emerg. / Night Light Circuit		LP835 3500K 80+ CRI	C110 Painted Silver to Match Anodized Aluminum Finish	ELH EM Through Wire w/ Separate Feed	F1A T-Bar Ceiling (UMB with Integrated J-Box)	21 21"	MCS Matching Feed Canopy at Support
EN Emerg. Battery Pack w/ Night Light Circuit		LP735 3500K 70+ CRI	C099 Custom Color (consult factory)	ELS EM Through Wire w/ Single Feed	F2 Hard Ceiling (Horizontal J-Box)	24 24"	OJB Offset J-Box at Feed Location
		LP741 4100K 70+ CRI		ELS2 Normal Feed w/ EM Separate Nuetral (Dual Feed Cord)	F3 Rigid Stem (10CRM only)	XX XX"	
		T8 only:		GLR Fusing (Fast Blow)	F4A IDS Clip 1/16" Tee		
		LP830P 3000K 80+ CRI Premier		GMF Fusing (Slow Blow)	F4B IDS Clip 9/16" Tee		
		LP835P 3500K 80+ CRI Premier		NYC New York City Code	F4C IDS Clip Screw Slot		
		LP841P 4100K 80+ CRI Premier		SCEP Sculptured End Cap			

Cerra Wall

SPECIFICATIONS

CONSTRUCTION

Die-formed cold-rolled steel housing. Flat steel end plate standard.
Die-cast aluminum end cap optional.

SHIELDING

Die-punched square windows on CRW2. Perforated steel windows on CRW3. White painted steel baffle with optional perforated housing on CRW4. Partially perforated steel housing on CRW7. Opal acrylic diffuser overlay standard on all fixtures.

REFLECTORS

Die-formed specular aluminum or pre-painted white steel.

FINISH

Fine textured white polyester powder paint standard, custom colors available.

FIXTURE LENGTH

4', 8' and 12' individual fixture sections. Add $\frac{1}{16}$ " for each standard end cap or 4" for each optional sculptured end cap to determine total fixture length. Using internal joiners, 4', 8' and 12' sections can be joined to form longer length fixtures.

OPTIONS



QUICKSHIP


Products shown with QuickShip icons are part of our express product selection. Go to www.peerless-lighting.com for details.



CONFIGURATIONS

Inside and outside corner and tenon connectors available for configurations. For inspiration see pages 198-199. Additional pattern connector details available at www.peerless-lighting.com.


DIMENSIONS / LAMPING



CRW

(1,2) T5, T5HO, T8

PERFORMANCE



CRW7 with WHR (1) T5HO

98.1% Indirect

1.9% Direct

75.5% Efficiency

For complete photometric data see specification sheets at www.peerless-lighting.com.

ORDERING INFORMATION

Fixture	# of Lamps in Cross Section	Lamp Type	Shielding (CRW4 only)	Reflector	Nominal Row Length*	Maximum Section Length	Voltage	Ballast Type	▶▶▶
CRW1	1	54T5HO	(Blank) None	WHR	_____ FT	R4 4'	120	GEB	<20% THD Electronic (T8 only)
CRW2	2	28T5	PERF Perforations above baffle	White Reflector (Standard)	*Must be in 4' increments.	R8 8'	277	GEB10	<10% THD Electronic Ballast
CRW3		32 (T8)		SPR Specular Reflector		R12 12'	347	ADEZ ^{1,2,3}	Advance Mark 10 dim
CRW4								ECO10 ¹	Lutron ECO-10 dim
CRW7								OSDIM ^{1,2,3}	Osram 0-10V dim
								TUDA ^{1,4}	ULT (0-10v) dim
									1 Not available in 347 Volt
									2 Not available with 28T5
									3 Not available with 32T8
									4 Not available with 54T5HO Lamp Type
									Reference ballast chart on web site or consult factory for other options.



Sample Catalog Number: CRW1 1 54T5HO WHR 40FT R12 277 GEB10 SCT LP835 C210 SCEP

CRW1 Cerra Wall Indirect**CRW2** Cerra Wall Indirect/Open**CRW3** Cerra Wall Lightvent**CRW4** Cerra Wall Indirect/Direct**CRW4** Cerra Wall Indirect/Direct with Perf**CRW7** Cerra Wall Partial Perf

# of Emergency Modules	Emergency Type	Switching	Lamp Color	Finish	General Options
(Blank) None 1SE 1 Section 2SE 2 Sections XSE X Sections	(Blank) None EL Emergency Battery Pack EC Emergency/ Night Light Circuit EN Emergency Battery Pack with Night Light Circuit	SCT Single Circuit DCT Dual Circuit	L/LP No lamp LP830 3000K 80+ CRI LP835 3500K 80+ CRI LP841 4100K 80+ CRI T8 only: LP730 3000K 70+ CRI LP735 3500K 70+ CRI LP741 4100K 70+ CRI T5 only: LP830P 3000K 80+ CRI Premier LP835P 3500K 80+ CRI Premier LP841P 4100K 80+ CRI Premier <i>Reference Lamp Chart on website or consult factory for other options.</i>	C110 Painted Silver to Match Anodized Aluminum Finish C210 Textured White White (Low Gloss) C099 Custom Color	DL Damp Location Label DU Dust Cover ELH EM Through Wire w/ Separate Feed ELS EM Through Wire w/ Single Feed ELS2 Normal Feed w/ EM Separate Neutral (Dual Feed Cord) GLR Fusing (Fast Blow) GMF Fusing (Slow Blow) NYC New York City Code SCEP Sculptured End Cap



www.peerless-lighting.com

PEERLESS LIGHTING ▪ Box 2556, Berkeley, CA 94702-0556 ▪ **Tel:** 510.845.2760 ▪ **Fax:** 510.845.2776

© 2009 Acuity Brands Lighting, Inc. All Rights Reserved. "Peerless" is a registered trademark, and "Cerra" is a trademark of Acuity Brands Lighting. Products in this brochure may be covered by one or more U.S. Patents and Patents Pending. Peerless Lighting reserves the right to change materials or modify the design of its product without notification as part of the company's continuing product improvement program.

An **Acuity** Brands Company