



# Lightedge®

## Indirect T8

Type:

Project:

### SPECIFICATIONS

Pendant Mount — Modular / 7" x 2 1/2" Deep Angular

EGAM1


### CATALOG NUMBER

FT

Examples: EGAM1 2 32 12FT R12 277 GEB10 DCT L/LP F2/15 C100 ACG

### AVAILABLE FIXTURES

#### EGAM1 - 2



### SPECIFICATIONS

#### Construction

Housing and endcap AA 6063 T6 extruded aluminum forming a 7" x 2 1/2" angular channel.

#### Reflectors

Die-formed reflectors with baked white enamel finish (nominal reflectance 90%).

#### Finish

Satin anodized standard; custom colors available.

#### Electrical

Specify 120 volt, 277 volt, or 347 volt. C-UL listed and labeled. For special circuiting, consult factory.

#### Fixture Length

4', 8' and 12' lengths in a single section for exact suspension spacing of 4', 8' and 12'. For total fixture length add 4" for each end-cap. Using internal joiners,

4', 8' and 12' sections can be joined to form longer-length fixtures.

### ORDERING LOGIC

Use guide below to order complete fixture runs from four feet to one-hundred feet in increments of four.

FT								▶▶▶	
Fixture	# of Lamps in Cross Section	Lamp Type	Nominal Row Length <sup>1</sup>	Maximum Section Length	Voltage	Ballast Type	# of Emergency Modules <sup>2</sup>		
EGAM1	2	32 32W 4' T8		R4 4' section R8 8' section R12 12' section	120 277 347	GEB Generic Electronic Ballast GEB10 <10% THD ELECTRONIC ADEZ <sup>4</sup> Advance Mark 10 dimming ECO10 <sup>4</sup> Lutron ECO-10 dimming ADZT <sup>4</sup> Advance Mark 7 0-10v dimming  Reference <a href="#">Ballast Chart</a> on website or consult factory for other options.	Blank 1SE 1 section 2SE 2 sections XSE X sections		
▶▶									
/									
Emergency Type <sup>3</sup>	Switching	Lamp Color	Mounting Type	/	Overall Suspension	Finish	Options		
Blank	SCT Single Circuit DCT Dual Circuit	L/LP No Lamp LP730 3000k 70+ CRI LP735 3500k 70+ CRI LP741 4100k 70+ CRI LP830 3000k 80+ CRI LP835 3500k 80+ CRI LP841 4100k 80+ CRI  Reference <a href="#">Lamp Chart</a> on website or consult factory for other options.	F1 T-Bar Ceiling (Universal Mounting Bracket) F1A T-Bar Ceiling (UMB with Integrated J-Box) F2 Hard Ceiling F4A Horizontal J-box F4B Grid Ceiling IDS 15/16" F4C Grid Ceiling IDS 3/16" Grid Ceiling IDS Screw Slot		12 12" overall suspension 15 15" overall suspension 18 18" overall suspension 21 21" overall suspension 24 24" overall suspension XX XX" overall suspension	C100 Satin Anodized Finish (Standard) C099 Custom Color (consult factory) C200 Peerless Standard White (Low Gloss) C005 Soft White (Low Gloss) C032 White White (Gloss) C041 White White (Low Gloss)	ACG Adjustable Cable Grippers CP Chicago Plenum DL Damp Location Label DU Dust Cover GLR Fast Blow Fuse GMF Slow Blow Fuse ELH EM Through Wire Harness ELS EM Through Wire Harness With Single Feed APF Alternate Power Feed (F4X mounting only)		
Notes:									
1 Must be in 4' increments.									
2 Sections per run; optional.									
3 EL, EN and EC not available with DCT in 4' sections.									
4 Not available in 347 volt.									

# Lightedge®

## Indirect T8

Type:


Project:

### PHOTOMETRICS

Pendant Mount — Modular / 7" x 2 1/2" Deep Angular

EGAM1

### 2-LAMP T8



APPROVED BY: 

TESTED IN ACCORDANCE WITH IES PROCEDURES, TEST DISTANCE EXCEEDS 25.0 FEET