


Project:

EGCM1


FT

Examples: EGCM1 3 54T5HO 12FT R12 277 GEB10 DCT L/LP F2/15 C100 ACG


EGCM1 - 1



EGCM1 - 2



EGCM1 - 3



Construction

Housing and endcap AA 6063 T6 extruded aluminum forming a 7" x 2 1/4" curvilinear channel.

Reflectors

Die-formed hammertone specular aluminum reflectors with baked white enamel finish.

Finish

Satin anodized standard; custom colors available.

Electrical

Specify 120 volt, 277 volt, or 347 volt. C-UL listed and labeled. For special circuiting, consult factory.

Fixture Length

4', 8' and 12' lengths in a single section for exact suspension spacing of 4', 8' and 12'. For total fixture length add 4" for each end-cap. Using internal joiners, 4', 8' and 12' sections can be joined to form longer-length fixtures.

ORDERING LOGIC

Use guide below to order complete fixture runs from four feet to one-hundred feet in increments of four.

An **Acuity** Brands Company

Lightedge®

Indirect T5 / T5HO

PHOTOMETRICS

Pendant Mount — Modular / 7" x 2 1/4" Deep Curved

EGCM1

Type:


Project:

1-LAMP T5HO

FAR-FIELD PHOTOMETRY

REPORT NUMBER: 5456 DATE: 11-15-2001

CATALOG NUMBER: EGCM1-1-54T5HO
LUMINAIRE: 7" W X 2 1/4" H ALUMINUM INDIRECT LIGHT WITH
WHITE PAINTED AND HAMMERTONE REFLECTOR
LAMP(S): 1-FP54/835/HO RATED @ 5000 LUMENS
BALLAST: QT 1X54/120PHO
MOUNTING:
LUMEN TO CANDELA RATIO USED = 9.15
TOTAL INPUT WATTS = 120.5 AT 12.0 VOLTS
THE 0 DEGREE PLANE IS PARALLEL WITH THE LAMPS.



APPROVED BY:




BARE LAMP LUMEN VALUE IS RATED AT LAMP OPERATING TEMPERATURE INSIDE THE LUMINAIRE.
FOR DETAIL EXPLANATIONS, PLEASE SEE PEERLESS PUBLICATION # A62

2-LAMP T5HO

FAR-FIELD PHOTOMETRY

REPORT NUMBER: 5455 DATE: 11-15-2001

CATALOG NUMBER: EGCM1-2-54T5HO
LUMINAIRE: 7" W X 2 1/4" H ALUMINUM INDIRECT LIGHT WITH
WHITE PAINTED AND HAMMERTONE REFLECTOR
LAMP(S): 2-FP54/835/HO RATED @ 5000 LUMENS
BALLAST: QT 2X54/120PHO
MOUNTING:
LUMEN TO CANDELA RATIO USED = 9.15
TOTAL INPUT WATTS = 120.5 AT 12.0 VOLTS
THE 0 DEGREE PLANE IS PARALLEL WITH THE LAMPS.



APPROVED BY:




BARE LAMP LUMEN VALUE IS RATED AT LAMP OPERATING TEMPERATURE INSIDE THE LUMINAIRE.
FOR DETAIL EXPLANATIONS, PLEASE SEE PEERLESS PUBLICATION # A62

3-LAMP T5HO

FAR-FIELD PHOTOMETRY

REPORT NUMBER: 5454 DATE: 11-14-2001

CATALOG NUMBER: EGCM1-3-54T5HO
LUMINAIRE: 7" W X 2 1/4" H ALUMINUM INDIRECT LIGHT WITH
WHITE PAINTED AND HAMMERTONE REFLECTOR
LAMP(S): 3-FP54/835/HO RATED @ 5000 LUMENS
BALLAST: QT 1X54/120PHO & QT 2X54/120PHO
MOUNTING:
LUMEN TO CANDELA RATIO USED = 9.15
TOTAL INPUT WATTS = 179.6 AT 12.0 VOLTS
THE 0 DEGREE PLANE IS PARALLEL WITH THE LAMPS.



APPROVED BY:



BARE LAMP LUMEN VALUE IS RATED AT LAMP OPERATING TEMPERATURE INSIDE THE LUMINAIRE.
FOR DETAIL EXPLANATIONS, PLEASE SEE PEERLESS PUBLICATION # A62

*Use a 0.58 multiplier for T5.