



Lightedge®

Indirect T8

Type:

Project:

SPECIFICATIONS

Wall Mount — Modular / 7 1/2" x 2 1/4" Curved

EGCW1


CATALOG NUMBER

FT

Examples: EGCW1 1 32 40FT R12 120 GEB10 2SE EL SCT LP835 C100

AVAILABLE FIXTURES

EGCW1 - 1



SPECIFICATIONS

Construction

Housing and endcaps AA 6063 T6 extruded aluminum forming a 7 1/2" x 2 1/4" curvilinear channel.

Reflectors

Die-formed reflectors combine hammertone specular aluminum and baked white enamel (nominal reflectance 90%). Prismatic acrylic kicker lens on 1 lamp product.

Finish

Satin anodized standard; custom colors available.

Electrical

Specify 120 volt, 277 volt, or 347 volt. C-UL listed and labeled. For special circuiting, consult factory.

Fixture Length

4', 8' and 12' lengths in a single section. For total fixture length add 4" for each end-cap. Using internal joiners, 4', 8' and 12' sections can be joined to form longer-length fix.

ORDERING LOGIC

Use guide below to order complete fixture runs from four feet to one-hundred feet in increments of four. 2' and 3' sections available. For additional row length increments, consult factory.

FT							
Fixture	# of Lamps in Cross Section	Lamp Type	Nominal Row Length ¹	Maximum Section Length	Voltage	Ballast Type	# of Emergency Modules ²
EGCW1	1	32 32W 4' T8		R4 4' section R8 8' section R12 12' section	120 277 347	GEB Generic Electronic Ballast GEB10 <10% THD ELECTRONIC ADEZ ⁴ Advance Mark 10 dimming ECO10 ⁴ Lutron ECO-10 dimming ADZT ⁴ Advance Mark 7 0-10v dimming <i>Reference Ballast Chart on website or consult factory for other options.</i>	Blank 1SE 1 section 2SE 2 sections XSE X sections
Emergency Type ³		Switching	Lamp Color	Finish		Options	
EL Emergency Battery Pack		SCT Single Circuit	L/LP No Lamp	C100 Satin Anodized Finish (Standard)		GLR Fast Blow Fuse	
EC Emergency Circuit/Night Light		DCT Dual Circuit	LP730 3000k 70+ CRI	C099 Custom Color (consult factory)		GMF Slow Blow Fuse	
EN Emergency Battery Pack w/ Night Light Circuit			LP735 3500k 70+ CRI	C200 Peerless Standard White (Low Gloss)		ELH EM Through Wire Harness	
			LP741 4100k 70+ CRI	C005 Soft White (Low Gloss)		ELS EM Through Wire Harness With Single Feed	
			LP830 3000k 80+ CRI	C032 White White (Gloss)		EXT 3" Extended Mount	
			LP835 3500k 80+ CRI	C041 White White (Low Gloss)		DL Damp Location Label	
			LP841 4100k 80+ CRI			DU Dust Cover	
<i>Reference Lamp Chart on website or consult factory for other options.</i>							
Notes: 1 Must be in 4' increments. 2 Sections per run; optional. 3 EL, EN and EC not available with DCT in 4' sections. 4 Not available in 347 volt.							

Lightedge®

Indirect T8

Type:

Project:

PHOTOMETRICS

Wall Mount — Modular / 7 1/2" x 2 1/4" Curved

EGCW1


1-LAMP T8

FAR-FIELD PHOTOMETRY

DATE: 11-14-2001

REPORT NUMBER: 5508

CATALOG NUMBER: EGCW1-1-32
 LUMINAIRE: 7 1/2" W X 2 1/4" H ALUMINUM ASYMMETRIC INDIRECT LIGHT
 WITH WHITE PAINTED REFLECTOR AND KICKER LENS
 LAMP(S): F32T8/SP35 RATED ● 2850 LUMENS
 BALLAST: REL-1P32-SC
 MOUNTING:
 LUMEN TO CANDELA RATIO USED = 9.15
 TOTAL INPUT WATTS = 30.6 AT 12.0 VOLTS
 THE 0 DEGREE PLANE IS PERPENDICULAR TO THE LAMPS.



APPROVED BY:



TESTED IN ACCORDANCE WITH IES PROCEDURES, TEST DISTANCE EXCEEDS 25.0 FEET