



## LSR9QS, LAR9QS & LWR9QS

### specifications

CONSTRUCTION — Die-formed pre-painted steel housing.

SHIELDING — Parabolic semi-specular aluminum louvers on LSR9QS and LAR9QS.

REFLECTORS — Die-formed pre-painted white steel on LSR9QS and LAR9QS, and specular aluminum on LWR9QS.

FINISH — Black low-gloss finish or white low-gloss finish.

FIXTURE LENGTH — 2' and 4' individual fixture sections.

### dimensions / lamping



(1) T5 or T5HO

### light distribution



See Typical Application section for sample layouts.

### ordering logic

Sample Catalog Number: LSR9QS G 1 54T5HO LDL U4 120 GEB10 LP835

Fixture		Ceiling Type		# of Lamps in Cross Section	Lamp Type		Baffle <i>(LSR9QS and LAR9QS only)</i>		Reflector <i>(LWR9 only)</i>		Maximum Section Length		Voltage	Ballast Type		▶▶▶		
LSR9QS	Symmetric louver	G	Lay in grid	1	14T5	14W 2' T5	LDL	Low iridescent louver	HOL	Black metal diffuser round holes	U2	2' section(s)	120	277	GEB10	<10% THD Electronic (all lamp types) ADEZ Advance Mark 10 dim (54T5HO) OSDIM Osram 0-10V dim (54T5HO)		
LAR9QS	Asymmetric louver				28T5	28W 4' T5					U4	4' section(s)						
LWR9QS	Wall wash				24T5HO	24W 2' T5HO									54T5HO			

▶▶ Emergency Type¹		Lamp Color	Finish	Options			
(Blank)	None	L/LP	No lamps	C200	White (low gloss)	FLNGW	Flange kit (dry wall only) white
EL	Emergency battery pack	LP830	3000K 80+ CRI	FLNGB	Flange kit (dry wall only) black	GLR	Fusing (fast blow)
		LP835	3500K 80+ CRI	GMF	Fusing (slow blow)		
		LP841	4100K 80+ CRI	C201	Black (low gloss)		

Notes: 1 Only available with U4

PEERLESS®  
An Acuity Brands Company

