

Lightline® Direct Wall Symmetric T8

Type:

Project:

SPECIFICATIONS

Rectangular 3 5/8" x 4 1/16"


LLWS

CATALOG NUMBER

FT

Examples: LLWS D 1 28T5 SSB 40FT R8 277 GEB10 SCT LP835 C100 - LLWS X 1 28T5 WPB 40FT R8 120 GEB10 1SE EC SCT LP835 C041

AVAILABLE FIXTURES



SPECIFICATIONS

Construction

Extruded aluminum housing forms a 3 5/8" x 4 1/16" rectangular channel. Die-cast aluminum end caps mechanically attach with no exposed fasteners. Extended arm mount (option "X") is extruded aluminum extending 21".

Reflectors

White painted reflector system.

Shielding

Arc-shaped, parabolic low iridescent semi-specular or white painted aluminum louver.

Finish

Satin anodized finish consists of satin anodized housing with end caps painted to match.

Electrical

Specify 120, 277 or 347 volt. Pre-wired with 16awg. fixture wire. For special circuiting or wire gauge, consult factory. Plug-in electrical connectors included. C-UL listed and labeled.

Fixture Length

4', 8', and 12' lengths in a single section. For total fixture length, add 7/8" for each end cap. Using internal joiners, 4', 8', and 12' sections can be joined to form longer length fixtures.

ORDERING LOGIC

FT									▶▶▶		
Fixture LLWS	Mounting Type	# of Lamps in Cross Section	Lamp Type	Baffle	Nominal Row Length ¹	Maximum Section Length	Voltage	Ballast Type			
	D Wall Spacer X 21" extended arm mount	1	32 T8	SSB Semi Specular WPB White Baffle	__FT	R4 4' Section R8 8' Section R12 12' Section	120 277 347	GEB10 <10% THD ELECTRONIC Dimming Ballasts Available: ADEZ ² Advance Mark 10 ADZT ² Mark 7 (0-10 Volt) ECO10 ² Lutron ECO-10 SS ² SIMPLY5™ Reference Ballast Chart on website or consult factory for other options.			
▶▶											
# of Emergency Modules	Emergency Type ³	Switching	Lamp Color	Finish	Options						
(Blank) None 1SE 2SE XSE	(Blank) None EL ^{2,4} Emergency Battery Pack EC Emergency Circuit EN ^{2,4} Emergency Battery Pack w/ Night Light	SCT Single Circuit	L/LP No Lamp LP730 3000K 70+ CRI LP735 3500K 70+ CRI LP741 4100K 70+ CRI LP830 3000K 80+ CRI LP835 3500K 80+ CRI LP841 4100K 80+ CRI Reference Lamp Chart on website or consult factory for other options.	C100 Satin Anodized Finish C041 White White (low gloss) C099 Custom Finish	DL Damp Location Label ELH EM Through Wire Harness ELS EM Through Wire Harness with Single Feed ELS2 Normal feed w/ EM separate neutral GLR Fast Blow Fuse GMF Slow Blow Fuse NYC New York City Code						
Notes:											
1 Must be in 4' increments. (Consult factory for additional increments).											
2 Not available in 347 volt.											
3 Emergency type is installed in the last 4' of fixture sections. Separate feed unless ELS/ELH is specified.											
4 Not available with DL option.											