



Mino LED Direct/Pendant

Type:

Project:


SPECIFICATIONS

23" x 23" x 3 3/4"

MN9

AVAILABLE FIXTURES

□ MN9



SPECIFICATIONS

Construction

Extruded aluminum with mitered corners forms housing.

Source

Two LED color temperature options — 3500K or 4000K — both within 2.5 MacAdam ellipses.

Lens

Clear 3/8" acrylic, high-performance lens fastened with thumb screws and magnets.

Finish

Painted aluminum is standard.

Electrical

LED light engine consists of modular LED boards and 0-10V dimmable driver rated for 50,000 hours (L80) at 25°C ambient temperature.

Specify MVOLT for 120V-277V or 347V with transformer. Pre-wired with 16AWG fixture wire. For special circuiting or wire gauge, consult factory.

Validation

CSA/CUS listed. FCC part 15 certified. LM-79 tested. Lighting Facts partner. DesignLights Consortium qualified luminaire.

Warranty

Five-year warranty includes fixture construction, LED light engine and driver. Terms and conditions apply.

Packaging

100% post-consumer recycled box and protective lens cover. 100% recycled cardboard inserts and kraft tape.

CATALOG NUMBER


Examples: MN9 35L MVOLT D38 LP835 F3C/12 C311 — MN9 35L 347 D38 LP840 F3C/24 C312 GMF

Fixture	Ceiling Type	Light Output	Voltage	Driver Type	LED Color Temperature	Mounting Type	Overall Suspension ¹	Finish	Options
MN9	(Blank)	35L 3500 Nominal delivered lumens	MVOLT 120V-277V 347 347V	D38 38W maximum	LP835 3500K 80+ CRI LP840 4000K 80+ CRI	F3C/ Swivel stem	12 12" 18 18" 24 24" 36 36" 48 48"	C311 Painted aluminum C312 White (satin) C099 Custom finish	GLR Fusing (fast blow) GMF Fusing (slow blow)


Notes:

¹ Consult factory for custom suspension lengths

PHOTOMETRICS Actual performance may differ as a result of end-user environment and application.



35L LP835
93 lumens per watt
3491 delivered lumens
100% down



35L LP840
93 lumens per watt
3505 delivered lumens
100% down

Mino LED

Direct/Pendant

Type:


Project:

23" x 23" x 3 3/4"

MN9

LIGHTING FACTS

MN9 35L LP835



MN9 35L LP840

