

NRM9QS

specifications

CONSTRUCTION — Nominal 4 1/2"W x 2 1/4"H for T5/T5HO and 5 1/4"W x 2 3/4"H for T8, extruded aluminum housing. Die-cast aluminum end cap.


SHIELDING — Frosted acrylic diffuser.

REFLECTORS — Semi-specular high reflectance aluminum or high reflectance white painted steel. Select semi-specular (SPR) for a wide distribution and maximum row spacing. Select white (WHR) for narrow applications (i.e. corridors) to soften side wall shadows.


FINISH — White polyester powder painted.

FIXTURE LENGTH — 4' and 8' lengths in a single section. For total fixture length add 1/2" for each standard end cap or 4 1/2" for each sculptured end cap (T5/T5HO only). Using internal joiners, 4' and 8' sections can be joined to form longer rows.

dimensions / lamping



(1,2,3) T5, T5HO



(1,2) T8

light distribution



I/D

See Typical Application section for sample layouts.

ordering logic

Sample Catalog Number: NRM9QS 2 28T5 SPR FST 40FT R8 277 GEB10 DCT LP835 F1/18 C041

Fixture	# of Lamps in Cross Section	Lamp Type	Reflector	Shielding	Fixture Row Length	Maximum Section Length	Voltage	Ballast Type	# of Emergency Modules	▶▶▶
NRM9QS	1 2 3'	28T5 28W T5 54T5HO 54W T5HO 32 T8	WHR White reflector SPR Specular reflector	FST Frosted diffuser	X FT (4' increments)	R4 4' section(s) R8 8' section(s)	120 277	GEB10 <10% THD Electronic (all lamp types) OS5C Osram 0-10V dim or line voltage control (32 T8) ADEZ Advance Mark 10 dim (54T5HO) OSDIM Osram 0-10V dim (54T5HO)	(Blank) None 1SE 1 section 2SE 2 sections XSE X sections	
▶▶ Emergency Type ²	Switching	Lamp Color	Mounting Type	/	Overall Suspension ⁴	Finish	Options			
(Blank) None EC ³ Emergency circuit EL Emergency battery pack EN ³ Emergency battery pack w/night light circuit	SCT Single circuit DCT ² Dual circuit	L/LP* No lamp LP830 3000K 80+ CRI LP835 3500K 80+ CRI LP841 4100K 80+ CRI <i>*Wired for full wattage lamps only, do not install low wattage lamps</i>	F1/ T-bar ceiling (universal mounting bracket) F1A/ T-bar ceiling (UMB with integrated J-box) F2/ Hard ceiling (horizontal J-box)		12 12" 15 15" 18 18" 21 21" 24 24" XX XX" <i>Overall suspension is measured from ceiling to bottom of fixture</i>	C041 White white (low gloss)	ACG Adjustable cable grippers CP Chicago plenum (available with F1A only) DU ⁵ Dust cover ELH Emergency through wiring w/separate feed ELS ³ Emergency through wiring w/single feed, shared neutral ELS2 ³ Emergency through wiring w/single feed, separate neutrals GLR Fusing (fast blow) GMF Fusing (slow blow) MCS Matching feed canopy at support OJB Offset junction box			

Notes: 1 Not available with 32 T8 lamps 2 Emergency type is installed in last 4' of fixture sections. Separate feed required unless ELS or ELS2 is specified
3 Not available with dimming 4 Maximum of 240" 5 Not available with 3 54T5HO lamps

PEERLESS®
An Acuity Brands Company

