



Cove not included.

Peerless® Cove

T8

Type:

Project:

SPECIFICATIONS

Cove


7ECXM5 / 9ECXM5

CATALOG NUMBER


Examples: 7ECXM5 2 32 U4 120 GEB SCT LP835 — 7ECXM5 2 17 U2 277 GEB10 SCT L/LP

AVAILABLE FIXTURES


7ECXM5 - 1




7ECXM5 - 2



9ECXM5 - 1



9ECXM5 - 2



SPECIFICATIONS

Construction

Housing one-piece cold rolled sheet steel with die-formed end plate forming a 7 1/4" x 3 3/4" (7ECXM5) and 8 3/4" x 2 3/4" (9ECXM5) rectangular channel.

Reflectors

Reflectors combine hammertone specular aluminum and baked white enamel (nominal reflectance 86%). Optical system includes micro-prismatic, 100% virgin acrylic specular/diffusing optical lens.

Finish

Baked white enamel.

Electrical

Specify 120 volt, 277 volt or 347 volt. Pre-wired with prescribed circuits as specified. C-UL listed. Listed and labeled to comply with Canadian standards. For special circuiting, consult factory.

ORDERING LOGIC

							▶▶▶
Fixture	# of Lamps in Cross Section	Lamp Type	Section Length	Voltage	Ballast Type	Emergency Type	
7ECXM5	1	32 4' 32WT8	U2 2'	120	GEB Generic Electronic Ballast	Blank	
9ECXM5	2	25 3' 25WT8	U3 3'	277	GEB10 10% THD Ballast	EL Emergency Battery Pack	
		17 2' 17WT8	U4 4'	347	Dimming Ballasts Available	EC Emergency Circuit	
			U8 8'	MVOLT ¹	2W5 Lutron Tu-Wire (120v only)	EN Emergency Battery Pack w/Night Light	
					ADEZ ² Advance Mark 10 (Powerline)		
					ECO10 ² Lutron (ECO-10)		
					DMHL ² Lutron Hi-Lume (FDB)		
					ADZT ² Advance Mark 7 (0-10 volt)		
					Reference Ballast Chart on website or consult factory for other options.		
▶▶							
Switching		Lamp Color	Options				
SCT	Single Circuit	L/LP No Lamp	RIF2	Radio Interference Filter			
DCT	Dual Circuit	LP730 3000k 70+ CRI	GLR	Fast Blow Fuse			
		LP735 3500k 70+ CRI	GMF	Slow Blow Fuse			
		LP741 4100k 70+ CRI	DU	Dust Cover			
		LP830 3000k 80+ CRI	DL	Damp Location Label			
		LP835 3500k 80+ CRI	NYC	New York City Code			
		LP841 4100k 80+ CRI					
		Reference Lamp Chart on website or consult factory for other options.					
Notes:							
1 Not for use when specifying battery pack.							
2 Not available in 347 volt.							

Peerless® Cove

T8

PHOTOMETRICS

Cove


Type:

Project:


7ECXM5 / 9ECXM5

1-LAMP T8 / 7ECXM5

2-LAMP T8 / 7ECXM5




TESTED IN ACCORDANCE WITH IES PROCEDURES, TEST DISTANCE EXCEEDS 25.0 FEET




TESTED IN ACCORDANCE WITH IES PROCEDURES, TEST DISTANCE EXCEEDS 25.0 FEET

1-LAMP T8 / 9ECXM5

2-LAMP T8 / 9ECXM5



TESTED IN ACCORDANCE WITH IES PROCEDURES, TEST DISTANCE EXCEEDS 25.0 FEET



TESTED IN ACCORDANCE WITH IES PROCEDURES, TEST DISTANCE EXCEEDS 25.0 FEET