

Olympia Micro™ *ClimaPlus*™



10

Year Availability

4211, 4221, 4231, 4411, 4421, 4742, 4744

HRC

High Recycled Content



OLYMPIA MICRO Panels with *CLIMAPLUS* Superior Performance
DONN FINELINE DXF Suspension System

See LEED report tool at usgdesignstudio.com
for detailed sustainability information.

Features and Benefits

- Nondirectional pattern reduces installation time and waste
- Economical, fine-textured panel
- Excellent light reflective finish (LR - .86) reduces light fixtures and energy use
- Available in Optimized Recycled Content formulations to help maximize LEED recycled content contribution
- Available with .60 NRC to assist in addressing HIPAA requirements (excludes items 4750 & 4751)
- *CLIMAPLUS* 30-year lifetime system warranty against visible sag, mold and mildew

Applications

- Offices
- Healthcare – HIPAA Requirements (.60 NRC)
- Classrooms
- Reception/Lobby areas
- Hotels
- Conference areas
- Retail stores

Substrate

- Water-felted mineral fiber



Fine-textured panel

To order samples, go to usg.com



White

Olympia Micro™ ClimaPlus™

To order samples/literature:
 - Web: usg.com
 - E-mail: samplit@usg.com
 - Fax: 888.874.2348
 Technical Services: 800.USG.4YOU

Web Sites: usg.com
usgdesignstudio.com
sustainableceilings.com
seismicceilings.com

See usg.com for
 the most up-to-date
 product information.

30
 Year System Warranty
 - No visible sag
 - Mold/mildew protection

	Edge	Panel Size	Class	Item No.	UL Classified				Color	Grid Options	VOC ⁷ Emissions	Anti-Mold & Mildew	Recycled Content ¹				Panel Cost
					NRC ⁵	CAC Min. ³	LR ²						Total	PC	PI	LEED RC	
OLYMPIA MICRO ClimaPlus, unperforated	SQ	2'x2'x5/8"	Class A	4210	-	35	.86	White	A, B, C	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
		2'x4'x5/8"	Class A	4913	-	35	.86	White	A, B	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
OLYMPIA MICRO ClimaPlus Panels .50 NRC⁵	SQ	2'x2'x5/8"	Class A	4211	.50	30	.86	White	A, B, C	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
		2'x4'x5/8"	Class A	4411	.50	30	.86	White	A, B	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
		2'x4'x5/8"	Class A	4411HRC	.50	35	.86	White	A, B	Low	●	54.5% ^{HRC}	45.4%	9.1%	49.9%	\$\$	
	SLT	2'x2'x5/8"	Class A	4221	.50	35	.86	White	D	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
		2'x2'x5/8"	Class A	4221HRC	.50	35	.86	White	D	Low	●	54.5% ^{HRC}	45.4%	9.1%	49.9%	\$\$	
		2'x4'x5/8"	Class A	4421	.50	35	.86	White	D	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
		2'x4'x5/8"	Class A	4421HRC	.50	35	.86	White	D	Low	●	54.5% ^{HRC}	45.4%	9.1%	49.9%	\$\$	
	FLB	2'x2'x5/8"	Class A	4231	.50	35	.86	White	E, F, G, H	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
		2'x2'x5/8"	Class A	4231HRC	.50	35	.86	White	E, F, G, H	Low	●	54.5% ^{HRC}	45.4%	9.1%	49.9%	\$\$	
		2'x4'x5/8"	Class A	4431	.50	35	.86	White	E, F, G, H	Low	●	45%	14.5%	30.5%	29.7%	\$\$	
OLYMPIA MICRO ClimaPlus Panels .60 NRC⁵	SQ	2'x2'x3/4"	Class A	4750	.60	33	.86	White	A, B, C	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
		2'x4'x3/4"	Class A	4751	.60	33	.86	White	A, B	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
	SLT	2'x2'x3/4"	Class A	4752	.60	35	.86	White	D	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
		2'x4'x3/4"	Class A	4753	.60	35	.86	White	D	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
	FLB	2'x2'x3/4"	Class A	4754	.60	35	.86	White	E, F, G, H	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
		2'x4'x3/4"	Class A	4755	.60	35	.86	White	E, F, G, H	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
OLYMPIA MICRO ClimaPlus Illusion Two/24 Panels The look of 2'x2' panels	SLT ³	2'x4'x3/4"	Class A	4742	.50	35	.86	White	D	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	
	ILT ⁴	2'x4'x3/4"	Class A	4744	.50	35	.86	White	I, J	Low	●	61% ^{HRC}	14%	46.9%	37.5%	\$\$	

Illusion Two/24

Patterns



Legend

Low Emissions (VOC)

Low-Emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on CHPS data base for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.

ClimaPlus Superior Performance⁶

Contains a broad-spectrum antimicrobial treatment on the face and back of the panel that provides guaranteed resistance against the growth of mold and mildew.

High Recycled Content

Classified as containing greater than 50% total recycled content. Total recycled content is based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

	A DX®/DXL™	B DXW™	C ⁹ CENTRICITEE™ DXT	D DX/DXL	E CENTRICITEE DXT	F IDENTITEE™ DXI™	G FINELINE® DXF	H FINELINE® 1/8 DXFF	I CENTRICITEE DXT	J IDENTITEE™ DXI™
Grid Profile Options										

Physical Data/ Footnotes

Product literature
Data sheet: SC2180

ASTM E1264 classification
Type III, Form 2, Pattern CE

ASTM E84 surface burning characteristics
Class A
Flame spread: 25
Smoke developed: 50

Weight
.78-1.03 lb./sq. ft.

Thermal resistance
R-1.4 (5/8" panels)
R-1.7 (3/4" panels)

Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a soft brush or vacuum.

Footnotes

- For details, see LEED report tool at usgdesignstudio.com.
- LR values are shown as averages.
- Panels have 15/16" routing.
- Panels have 9/16" routing.
- Mixing .50 and .60 NRC panels in the same ceiling plane is not recommended.
- Panel face and back surfaces treated with a proprietary, broad-spectrum antimicrobial standard

formulation that inhibits and retards the growth of mold and mildew. For details, see *Ceiling Systems Limited Warranty Commercial Applications* (SC2102) and *ClimaPlus Ceilings Certification of Performance* (SC2451).



Manufactured by USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CENTRICITEE, ClimaPlus, DONN, DX, DXF, DXFF, DXI, DXL, DXW, FINELINE, IDENTITEE, OLYMPIA Micro, USG, USG in stylized letters.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC2180/rev. 5-12
© 2012 USG Interiors, LLC
Printed in U.S.A.