

SHEETROCK™ Lay-In Ceiling Panel *ClimaPlus*™

USG

10

Year Availability
3270



SHEETROCK Lay-In Ceiling Panel, Vinyl, with CLIMAPLUS Performance/
Donn ZXLA Suspension System

Features and Benefits

- CLEAN ROOM™ panels can be used in clean room environments up to class 100
- Washable and scrubbable finish—impact and scratch resistant
- Panels meet USDA/FSIS requirements for food processing areas
- CLIMAPLUS™ 30-year lifetime no-sag system warranty

Applications

- Kitchens and food preparation areas
- Restrooms and utility areas
- Locker rooms
- Parking garages
- Exterior protected soffits

Substrate

- Gypsum panel

See LEED report tool at usgdesignstudio.com
for detailed sustainability information.

To order samples, go to usg.com



White

Smooth-textured panel - Vinyl (PVC)

SHEETROCK™ Lay-In Ceiling Panel *ClimaPlus™*

To order samples/literature:

– Web: usg.com

– E-mail: samplit@usg.com

– Fax: 888 874.2348

Technical Services: 800 USG.4YOU

Web Sites: usg.com

usgdesignstudio.com

sustainableceilings.com

seismicceilings.com

See usg.com for
the most up-to-date
product information.

30


Year System Warranty
– No visible sag

**SHEETROCK
Lay-In Ceiling
Panel *CLIMAPLUS*,
Vinyl**

Edge	Panel Size	Class ²	Item No.	NRC ³	CAC Min.	LR ⁴	Color	Abuse-Resistant	Grid Options	Recycled Content ¹	Panel Cost
SQ 	2'x2'x1/2"		3260	–	35	.77	White		A, B, C, D	40%	\$
	2'x4'x1/2"		3270	–	40	.77	White		A, B, C, D	40%	\$
SQ 	2'x4'x1/2"		3200	–	40	.77	White		A, B, C, D	40%	\$\$

A DONN® DX®/DXL™	B DONN® DXLA™	C ZXLA™	D DONN CE™6
------------------------	------------------	------------	----------------

**Grid Profile
Options**



Low Emissions (VOC)

Low-Emitting performance meets CA Specification 01350 (CA Dept. of Health Services Standard Practice for the testing of VOC emissions) and is listed on CHPS data base for low-emitting materials. USG Certificate of Compliance for Low VOC Emissions also available on usg.com.

Physical Data/ Footnotes

Product literature
Data sheet: SC1820

ASTM E1264 classification
Type XX, Pattern G

**ASTM E84 surface burning
characteristics**

Class A
Vinyl
Flame spread: 25
Smoke developed: 50
CLEAN ROOM
Flame spread: 25
Smoke developed: 50

Weight
1/2" = 2.00 lb./sq. ft.

Thermal resistance
1/2" = up to R-0.45

Maximum backloading
See Warranty for details.

Maintenance
Can be cleaned easily with a damp sponge. Use mild detergent and water – do not use acetate, ammonia or high concentration of chlorine, bromide or other harsh chemicals.

U.S. Coast Guard acceptance
Approved for use on merchant ships.

Footnotes

- For details, see LEED report tool at usgdesignstudio.com.
- Fire-rated items: see UL design details.
- NRC rating is .10. USG does not consider a ceiling panel to be acoustically rated if NRC is less than .50
- LR values are shown as averages.
- Field-cut edges of CLEAN ROOM panels must be sealed with white latex paint.
- Clean-room-rated applications require a suspension system with gasketed tee flanges such as DONN CE.



Manufactured by USG Interiors, LLC
550 West Adams Street
Chicago, IL 60661

The following are trademarks of USG Interiors, LLC or a related company: CE, CLEAN ROOM, *CLIMAPLUS*, DONN, DX, DXL, DXLA, FIRECODE, SHEETROCK, USG, ZXLA.

Safety First! Follow good safety/industrial hygiene practices during installation. Wear appropriate personal protective equipment. Read MSDS and literature before specification and installation.

SC1820/rev. 5-12
© 2012 USG Interiors, LLC
Printed in U.S.A.