DUNE™

Square Lay-in & Tegular

fine texture

10-YEAR Availability — Items 1772, 1773, 1774, 1775 & 1776

Dune with Prelude® XL® 15/16" Exposed Tee grid (Pg. 215);
Axiom® Classic Trim (Pg. 236)

Dune with Interlude® 9/16" Dimensional Tee grid (Pg. 211);
Axiom® Classic Trim (Pg. 236)

Key Selection Attributes

- Upgrade look at a modest price
- Ceiling-2-Ceiling™ Post-consumer Recycled Content options: Items 1773HRC, 1775HRC, 1774HRC, 1776HRC. 35% Pre-consumer; 18% Post-consumer
- Durable
  Scratch-resistant
- Non-directional visual reduces installation time and scrap
- 30-Year Limited System Warranty against visible sag (excludes items 1796 and 1798), mold/mildew, and bacterial growth

Typical Applications

- Offices
- Corridors
- Retail
- Hospitality
- Classrooms

Detail (Other Suspension Systems compatible. Refer to listing on page 156.)



Dune



Dune Square Lay-in with Prelude 15/16" Exposed Tee grid

Dune Tegular with Suprafine® 9/16" Exposed Tee grid



Dune Tegular with Interlude XL® 9/16" Dimensional Tee grid



Dune Tegular with Silhouette® 9/16" Bolt-Slot grid 1/4" Reveal

Color

White (WH)

DUNE™

Square Lay-in & Tegular

fine texture

CEILING-2-CEILING™ POST-CONSUMER RECYCLED CONTENT

The post-consumer recycled content of these items is from reclaimed ceilings

Recycled Content: Up to 53%

armstrong.com/greengenie

LEED® Credits

Energy	Waste Mgmt	Recycled Content	Local Materials	Renewable Materials	Daylight & Views
✔	✔	✔	✔	✔	✔

Location Dependent

LEED for Schools

Acoustics	Low Emitting or CHPS
	✔

35% Pre-consumer; 18% Post-consumer

$$$$$

Visual Selection

Performance Selection

Dots represent highest level of performance.

Edge Profile	Suspension Detail Dwg. Pgs. 226-228	Item No.	Dimensions		UL Classified Acoustics NRC	CAC	Fire Rating	Light Reflect	Sag Resist	Anti-Microbial	Durable	Recycle Program
DUNE Square Lay-in												
15/16" Square Lay-in	1	**1772** **1772M**	2' x 2' x 5/8" 600 x 600 x 15mm		0.50	30	Class A	0.83 •	HumiGuard+ •	BioBlock+ •	Scratch •	Yes •
	1	**1850** **1850M**	2' x 2' x 5/8" 600 x 600 x 15mm		0.50	35	Fire Guard	0.83 •	•	•	•	•
	1	**1773** **1773M** **1773HRC**	2' x 4' x 5/8" 600 x 1200 x 15mm		0.50	33	Class A	0.83 •	•	•	•	•
	1	**1851** **1851M**	2' x 4' x 5/8" 600 x 1200 x 15mm		0.50	35	Fire Guard	0.83 •	•	•	•	•
	1	**1796** **1796M**	20" x 5' x 3/4" 500 x 1500 x 19mm		0.50	35	Class A	0.83 •	Standard	•	•	•
	1	**1798** **1798M**	30" x 30" x 3/4" 750 x 750 x 19mm		0.50	35	Class A	0.83 •	Standard	•	•	•
DUNE Tegular												
9/16" Beveled Tegular	31-34, 54	**1775** **1775M** **1775HRC**	2' x 2' x 5/8" 600 x 600 x 15mm		0.50	35	Class A	0.83 •	•	•	•	•
	31	**1852**	2' x 2' x 5/8"		0.50	35	Fire Guard	0.83 •	•	•	•	•
	31-34, 54	**1777** **1777M**	2' x 4' x 5/8" 600 x 1200 x 15mm		0.50	35	Class A	0.83 •	•	•	•	•
15/16" Angled Tegular	6	**1774** **1774M** **1774HRC**	2' x 2' x 5/8" 600 x 600 x 15mm		0.50	35	Class A	0.83 •	•	•	•	•
	6	**1853**	2' x 2' x 5/8"		0.50	35	Fire Guard	0.83 •	•	•	•	•
	6	**1776** **1776M** **1776HRC**	2' x 4' x 5/8" 600 x 1200 x 15mm		0.50	35	Class A	0.83 •	•	•	•	•

Suspension Systems

15/16"



Prelude®

Prelude XL® Fire Guard

9/16"



Interlude® | Silhouette® Bolt-Slot | Sonata® | Suprafine® | Trimlok® Screw-Slot | Suprafine XL Fire Guard

Item 1775-CAC 33 on 9/16" Interlude, Sonata, Suprafine

Physical Data

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less. (UL labeled) Fire Guard™: A fire resistive ceiling when used in applicable UL assemblies

ASTM E1264 Classification
Type III, Form 2, Pattern C E
Fire Class A

Sag Resistance
HumiGuard® Plus – superior resistance to sagging in high humidity conditions up to, but not including, standing water and outdoor applications.

VOC/Formaldehyde Emissions
Meets CA Dept. of Health Services Standard Practice for the testing of VOC Emissions and is listed on CHPS High Performance Products Database for Low-Emitting Materials.

Anti Mold/Mildew & Bacteria
BioBlock® Plus contains an anti-microbial treatment and provides guaranteed resistance against growth of mold/mildew and Gram-positive and Gram-negative odor/stain-causing bacteria for 30 years.

Insulation Value
R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty Information
See warranty details in the back of this catalog

Weight; Square Feet/Carton
1772 – 0.94 lbs/SF; 64 SF/ctn
1773 – 0.88 lbs/SF; 80 SF/ctn
1796 – 1.33 lbs/SF; 67 SF/ctn
1798 – 1.14 lbs/SF; 50 SF/ctn
1850 – 1.19 lbs/SF; 48 SF/ctn
1851 – 1.22 lbs/SF; 64 SF/ctn
1774, 1775 – 0.75 lbs/SF; 64 SF/ctn
1776, 1777 – 0.75 lbs/SF; 80 SF/ctn
1852, 1853 – 1.20 lbs/SF; 48 SF/ctn