









Sustainability

CERTAINTEED CEILINGS / LEED® 2009 SUMMARY TABLE

LEED 2009: New Construction, Core and Shell, and Schools










Product Name	LEED Total Recycled Content, % ¹	Minimum Total Recycled Content %	Minimum Post-Consumer RC, %	Minimum Pre-Consumer RC, %	Weight, lbs/SF
Designer Series					
Adagio	31-38	36-62	15-27	9-47	1.60
Aquarock	0	0	0	0	2.00
Ecophon Focus	73	75	70	5	0.25-0.55
Ecophon Gedina	73	75	70	5	0.2-0.25
Ecophon Hygiene	73	75	70	5	0.25
Ecophon Master	73	75	70	5	0.45-0.65
Ecophon Super G	73	75	70	5	0.50
Envirogard	0	0	0	0	2.00
Gyptone BASE 31	45	85	5	80	1.84
Gyptone LINE 4	45	85	5	80	1.64
Gyptone POINT 11	45	85	5	80	1.64
Gyptone QUATTRO 20	45	85	5	80	1.64
TufCore	3-4	3-4	3-4	0	2.20
Performance Series					
Baroque	27-31	36-45	18	18-27	0.70
Protectone Baroque 	28	47	9	38	1.00
Baroque Customline	27-31	36-45	18	18-27	0.91
Protectone Baroque Customline 	28	47	9	38	1.30
Cashmere	39	74	4	70	0.95
Protectone Cashmere 	28	47	9	38	1.19
Cashmere Customline	39	74	4	70	1.06
Cashmere High NRC	39	74	4	70	0.95
Cashmere Style Edge	39	74	4	70	0.83
Directional Fissured	27-31	36-45	18	18-27	0.74
Protectone Directional Fissured 	28	47	9	38	1.00
Fine Fissured	27-31	36-45	18	18-27	0.70
Protectone Fine Fissured 	28	47	9	38	1.05
Fine Fissured Customline	27-31	36-45	18	18-27	0.91
Protectone Fine Fissured Customline 	28	47	9	38	1.30
Fine Fissured High NRC	39	74	4	70	0.95
Open Plan	37-44	37-44	37-44	0	0.34 ²
Sand Micro	27-31	36-45	18	18-27	0.78
Sand Micro Customline	27-31	36-45	18	18-27	0.91
School Board	31	45	18	27	0.81
Protectone School Board 	28	47	9	38	1.07
Symphony <i>f</i>	39-43	39-43	39-43	0	0.45 ²
Symphony <i>g</i>	0	0	0	0	2.00
Symphony <i>m</i>	38	72	4	68	0.96
Theatre Black <i>f</i>	33-39	33-39	33-39	0	0.23-0.34
Vantage 10	27-31	36-45	18	18-27	0.81
Protectone Vantage 10 	28	47	9	38	1.07
Versatone	41-42	41-42	41-42	0	0.15-0.23
Vinylrock	0	0	0	0	1.70
VinylShield A, C	27-28	46	9	37-38	1.00
CertainTeed Suspension					
Classic (stab & hook)	23	25	20	5	
Cloud Molding	50	75	25	50	

¹ LEED formula for recycled content = post consumer content + 1/2 pre-consumer content

² Weight based on 1-inch product thickness for fiberglass products with multiple thicknesses

Sustainability

CERTAINTEED CEILINGS / LEED® 2009 SUMMARY TABLE

		LEED 2009: New Construction, Core and Shell, and Schools				Exclusive to LEED 2009 for Schools	
Product Name		NRC	CAC	Light Reflectance (LR)	Recycle Program	Low-emitting or CHPS IEQ 4.6	Meets Minimum Acoustic Performance IEQ Prerequisite 3
Designer Series	Adagio	0.80-0.90	36-42	0.84-0.90			+
	Aquarock	—	40-42	0.78		+	
	Ecophon Focus	0.80	25	0.85	Pending	+	+
	Ecophon Gedina	0.85	19-21	0.84	Pending	+	+
	Ecophon Hygiene	.80-.85	21	0.84	Pending	+	+
	Ecophon Master	0.30-0.95	30-31	0.85	Pending	+	+
	Ecophon Super G	0.90	30	0.78	Pending		+
	Envirogard	—	38-40	0.78		+	
	Gyptone BASE 31	—	35	0.82		+	
	Gyptone LINE 4	0.70 ³	35	0.70		+	+
	Gyptone POINT 11	0.80 ³	35	0.71		+	+
	Gyptone QUATTRO 20	0.75 ⁴	35	0.71		+	+
	TufCore	0.65	38-40	0.82-0.90			Needs wall panels
Performance Series ( Protectone "Fire-Rated")	Baroque	0.60	33-35	0.83	+	+	Needs wall panels
	Protectone Baroque 	0.55	35-40	0.83	+	+	Needs wall panels
	Baroque Customline	0.50-0.60	38	0.83	+	+	Needs wall panels
	Protectone Baroque Customline 	0.50	40	0.83	+	+	Needs wall panels
	Cashmere	0.60	35	0.83	+	+	Needs wall panels
	Protectone Cashmere 	0.45	35	0.83	+	+	Needs wall panels
	Cashmere Customline	0.60	35	0.83	+	+	Needs wall panels
	Cashmere High NRC	0.70	30-32	0.82	+	+	Needs wall panels
	Cashmere Style Edge	0.60	31-35	0.83	+	+	Needs wall panels
	Directional Fissured	0.60	33-35	0.82	+	+	Needs wall panels
	Protectone Directional Fissured 	0.55	35-40	0.82	+	+	Needs wall panels
	Fine Fissured	0.60	33-35	0.84	+	+	Needs wall panels
	Protectone Fine Fissured 	0.55	35-40	0.84	+	+	Needs wall panels
	Fine Fissured Customline	0.50-0.60	38	0.84	+	+	Needs wall panels
	Protectone Fine Fissured Customline 	0.50	40	0.84	+	+	Needs wall panels
	Fine Fissured High NRC	0.70	35	0.83	+	+	+
	Open Plan	0.95 - 1.05	25-30	0.84			+
	Sand Micro	0.50	33-35	0.88	+	+	Needs wall panels
	Sand Micro Customline	0.50	35	0.88	+	+	Needs wall panels
	School Board	0.55	35	0.84	+	+	Needs wall panels
	Protectone School Board 	0.55	35-40	0.84	+	+	Needs wall panels
	Symphony <i>f</i>	0.80 - .95	22-25	0.90			+
	Symphony <i>g</i>	—	40-42	0.90		+	Needs wall panels
Symphony <i>m</i>	0.70	33-35	0.90	Pending	+	+	
Theatre Black <i>f</i>	0.75-0.90	20-25	—			+	
Vantage 10	0.60	33-35	0.83	+	+	Needs wall panels	
Protectone Vantage 10 	0.55	35-40	0.83	+	+	Needs wall panels	
Versatone	0.70	—	0.73-0.79			+	
Vinylrock	—	38-40	0.78		+		
VinylShield A, C	—	39-42	0.78		+	Needs wall panels	
CertainTeed Suspension	Classic (stab & hook)	NA	NA	NA		NA	
	Cloud Molding	NA	NA	NA		NA	

³ Gyptone with 3-1/2" CertaPro fiberglass insulation overlay.

⁴ Gyptone with 6" CertaPro fiberglass insulation overlay.