Product Specifications

WORKING OUT -- INFINITY MODULAR

MANNINGTON COMMERCIAL

PHYSICAL CONSTRUCTION:

CONSTRUCTION:	Patterned Loop
FACE FIBER:	Mannington Quantum Nylon
DYE METHOD:	Solution / Yarn
GAUGE:	1/12
STITCHES PER INCH:	7.83
PILE THICKNESS:	.108 imches
TUFTED YARN WEIGHT:	16 Ounces Per Square Yard
DENSITY:	Average Density = 5,333; Weight Density = 85,333
PRIMARY BACKING:	100% Woven Synthetic
PRIMARY PRECOAT:	100% Non-Aqueous Closed Cell Polymer, Providing Lifetime Warranty Against Stain Wick-Back
SECONDARY BACKING:	Infinity Modular Reinforced Composite Closed Cell Polymer
STANDARD SIZE:	24" X 24" Modular Tiles
INSTALLATION METHOD:	Random; Other Methods at Owner's Discretion

ENVIRONMENTAL:

RECYCLED CONTENT:	Contains Pre-Consumer Recycled Content*
MANUFACTURE LOCATION:	Calhoun, Georgia 30701 USA
NSF / ANSI-140 CERTIFICATION:	Gold
CRI GREEN LABEL PLUS ID:	GLP7616

WARRANTIES:

WARRANTY:	Lifetime Limited Warranty, Including Face Wear, Moisture Barrier, Wick-Back, Delamination, Tuft Bind, Unraveling, and Static Protection
STAIN RESISTANT WARRANTY:	SafeGuard SR with 10 Year Limited Warranty Against Staining

PRODUCT TESTING:

CRI TM101 APPEARANCE RATING:	Heavy Traffic
RADIANT PANEL (ASTM E-648):	Class I (Direct Glue)
SMOKE CHAMBER (ASTM-E-662):	Less than 450 (Flaming Mode)
METHENAMINE PILL TEST (ASTM D-2859):	Passes
DIMENSIONAL STABILTY AACHEN TEST:	Passes
ELECTROSTATIC PROPENSITY (AATCC 134):	Less than 3.0 KV

RECOMMENDED ADHESIVE:

RELEASEABLE ADHESIVE:	Mannington Infinity Pressure Sensitive Adhesive
CRI GREEN LABEL PLUS ID:	GLP70522
VOC LIMITS:	Meets SCAQMD Rule #1168
BOND WARRANTY:	Lifetime Limited Warranty When Used With Mannington Carpet

Specifications are subject to normal manufacturing variances. Specifications are subject to change without notice when technological advancements provide improved product performance.

* Please contact Mannington Technical Services at 1-800-241-2262 for updated, specific recycled content percentages for each product.