



Style Specifications — Contour Series

All floors shown or listed in this specification shall be Contour Series by Centiva, Florence, AL, 35630.

Specific product shall be: ___ - ___ - C ___ - ___ in size ___" x ___"
Style Color Series Surface Edge

The Centiva Contour Series shall be heterogeneous, resilient flooring with a .032" high density wearlayer. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each line. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700 and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose), or CENTI 2000 EP (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

*It is recommended that all Contour square tiles be installed tessellated or in one direction.
Additional sizes, surface textures, and edge treatments are available upon request.
Ask your Centiva consultant for more information.*

CONTOUR STONE – 0542-C Arcadian Column

| | | | |
|-----------------------------|---|-----------------------|-----------------------------|
| Classification: | ASTM F 1700 Class III Solid Vinyl Tile | | |
| Construction: | Layered product consisting of wearlayer, decorative film, and backing with pre- and post-consumer content | | |
| Overall Thickness: | .120" / 3 mm (nominal) | | |
| Wearlayer Thickness: | .032" clear, rigid high density PVC | | |
| Size: | 12" x 12" or 18" x 18" plus additional custom sizes | | |
| Edge: | Square Edge (SE) or Slight Bevel (SB) | | |
| Surface Texture: | Quarry (QU) recommended. Additional surface textures available upon request. | | |
| Warranty: | 20 years Commercial, Lifetime Residential | | |
| Recycling: | Suitable | | |
| Test Performance: | ASTM E 648 | Critical Radiant Flux | Class I CRF > 0.45 |
| | ASTM E 662 | Smoke Density | < 450 |
| | ASTM F 925 | Chemical Resistance | Excellent |
| | Slip Resistance | ADA Compliant | Varies with surface texture |
| | | FTC Slip Resistant | Classified Product |