

Style Specifications — Victory Series

All floors shown or listed in this specification shall be Victory Series by Centiva, Florence, AL, 35630.

Specific product shall be: __ __ V __ __ in size __ " x __ "
 Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" (.80 mm) high density wearlayer depending on product. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose) *(excluding Victory Magics, Coral Reef, and Mineral Chip products), or CENTI 2000 EP (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

VICTORY – CT 9141-V Light Iron

Classification:	ASTM F 1700 Class III Solid Vinyl Tile		
Construction:	Multiple layers with pre-consumer recycled backing		
Overall Thickness:	.120" / 3 mm (nominal)		
Wearlayer Thickness:	.032" clear, rigid high density PVC		
Size:	12" x 12", 12" x 18", 12" x 36", or 18" x 18" plus additional custom sizes		
Edge:	Square Edge (SE) or Slight Bevel (SB)		
Surface Texture:	Fresco (FC) recommended. Additional surface textures available upon request.		
Warranty:	20 years Commercial, Lifetime Residential		
Recycling:	Suitable		
Test Performance:	ASTM E 648	Critical Radiant Flux	Class I CRF>0.45
	ASTM E 662	Smoke Density	<450
	ASTM F 925	Chemical Resistance	Excellent
	Slip Resistance	ADA Compliant	Varies with surface texture
		FTC Slip Resistant	Classified Product