

## Style Specifications — Victory Series

All floors shown or listed in this specification shall be Victory Series by Centiva, Florence, AL, 35630.

Specific product shall be: \_ \_ \_ \_ 
$$\underline{\lor}$$
 \_ \_ \_ in size \_ "  $\times$  \_ "

Style Color Series Surface Edge

The Centiva Victory Series shall be homogeneous or constructed with a .032" (.80 mm) high density wearlayer depending on product. All products shall have an overall gauge of .120" (3 mm) nominal. See individual product specification for sizes offered in each style. The resilient tile shall be manufactured in accordance with ASTM Specification F-1700, and shall be asbestos free. All products shall have a Commercial Limited 20-year Wear Warranty and Residential Lifetime Wear Warranty. The adhesive shall be CENTI 2001 Wet Set, CENTI 6000 SP (Special Purpose) \*(excluding Victory Magics, Coral Reef, and Mineral Chip products), or CENTI 2000 EP (epoxy). Installation shall be in accordance with the latest Centiva Installation Guidelines.

## VICTORY - CT 9121-V Light Green

Classification: ASTM F 1700 Class III Solid Vinyl Tile

**Construction:** Multiple layers with pre-consumer recycled backing

Overall Thickness: .120" / 3 mm (nominal)

Wearlayer Thickness: .032" clear, rigid high density PVC

Size:  $12" \times 12"$ ,  $12" \times 18"$ ,  $12" \times 36"$ , or  $18" \times 18"$  plus additional custom sizes

**Edge:** Square Edge (SE) or Slight Bevel (SB)

Surface Texture: Fresco (FC) recommended. Additional surface textures available upon request.

Warranty: 20 years Commercial, Lifetime Residential

**Recycling:** Suitable

Test Performance: ASTM E 648 Critical Radiant Flux Class I CRF>0.45

ASTM E 662 Smoke Density <450
ASTM F 925 Chemical Resistance Excellent

Slip Resistance ADA Compliant Varies with surface texture

FTC Slip Resistant Classified Product