

Product Specifications
ABERDEEN COLLECTION (Axis & Classic)

MANNINGTON
COMMERCIAL

PHYSICAL CONSTRUCTION

Construction	Heterogeneous Light Commercial
Size	12' (3.66 m)
Wearlayer Thickness (Axis)	.012 inches (0.31 mm)
Wearlayer Thickness (Classic)	.010 inches (0.25 mm)
Overall Thickness (Axis)	.075 inches (1.91 mm)
Overall Thickness (Classic)	.060 inches (1.52 mm)
Weight Per Square Yard (Axis)	2.81 lbs (1.5 kg per m ²)
Weight Per Square Yard (Classic)	2.61 lbs (1.4 kg per m ²)
Roll - Min. – Max. (Axis)	55 sq. yds. (46.0 sq.m.) - 175 sq. yds. (146.3 sq.m.)
Roll – Min. – Max. (Classic)	55 sq. yds. (46.0 sq.m.) - 170 sq. yds. (142.1 sq.m.)
Static Load Limit	75 psi

ENVIRONMENTAL

Recycled Content (Axis)	Minimum 7% Recycled Content
Recycled Content (Classic)	Minimum 8% Recycled Content
FloorScore Indoor Air Quality	SCS Certified
CHPS 01350 Indoor Air Quality	Passed and Listed
Manufacture Location	Salem, NJ USA

TESTING

ASTM Specification F-1303 - (Axis)	Type 1, Grade 2, Class A
ASTM Specification F-1303 – (Classic)	Type 1, Grade 3, Class A
HUD/FHA Requirements	Exceeds
Static Coefficient of Friction (ASTM C1028)	Meets ADA Guidelines at 0.6
Flooring Radiant Panel Test (ASTM-E-648)	≥ .45 watts/cm ² , Passes (Class I)
N.B.S. Smoke Chamber Test (ASTM-E-662)	<450 - Passes

WARRANTIES

Warranty	Limited 10 Year Light Commercial Warranty Limited 15 Year Residential Warranty
----------	---

INSTALLATION

Installation Adhesive	Mannington V-81 / Full Spread*
Chemical Seam Sealer	MLG-33 Seam Sealer / VST-96 Applicator Kit

- Aberdeen is not recommended in commercial areas that require static dissipation.
- Aberdeen is not recommended in commercial areas where the surface temperature over radiant heated substrate exceeds 90° F.
- *Verify substrate (concrete) is dry per ASTM F-1869 3 lbs. maximum MVER or ASTM F-2170 75% maximum relative humidity.
- Dirt, wetness, and improper maintenance may cause significant variation in actual performance.
- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- Use entryway systems outside each entrance to prevent dirt, sand, grit, and other substances from being tracked onto floor.

Choices That Work

800 241 2262 manningtoncommercial.com