

## Bubble Mat

Ultimate anti-fatigue mat...dozens of air pockets provide all-day comfort

### PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	DATA
Manufacturing Process	Premium black molded rubber
Backing	Hollow "Air Dome" backing
PRODUCT DIMENSIONS	
Standard Mat Sizes	2' x 3', 3' x 4'
Overall Thickness	½"
PHYSICAL PROPERTIES	
Hardness (ISO 868/ASTM D2240)	65 ± 5 (°sh)
Density (ISO 2781)	1.25 ± 0.03 (g/cm <sup>3</sup> )
Tensile Strength (ISO 37/ASTM D412)	1136 PSI
Elongation (ISO 37)	300 %
Abrasion (ISO 4649/ASTM D1630)	< 200 (mm <sup>3</sup> )

### COMMON USES

- Work stations
- Cash Registers
- Service Counters
- Industrial Areas

### CLEANING & MAINTENANCE

**Dry Areas:** Sweep and then mop the Anti-Static/Anti-Fatigue Mat with a neutral cleaner. If needed, flush both sides of mat with warm water and a mild detergent to remove remaining dirt.

**Wet Areas:** Hose both sides of the mat with warm water and a mild detergent.

**Periodic Maintenance:** If severely soiled, scrub mat using a brush with a low foaming general purpose cleaner. Flush mat with hot water and allow to dry flat before placing it back into service.

*\*For more detailed procedures contact our trained Product Specialist or visit our website at [www.matsinc.com](http://www.matsinc.com)*

### WARRANTY

**Limited 1-Year Warranty.** Mats, Inc. guarantees its Anti-fatigue mats against deterioration due to faulty materials or workmanship. This guarantee does not cover damage that could occur from other abuses beyond the general intended application of the product. No other warranty is expressed or implied. Limit of liability from any losses resulting from the use of this product shall be for the purchase price only, and applied in form of credit, excluding any freight charges.