

Drain Tile

Versatile, very flexible anti-slip drainage mat provides safe footing in wet areas

PRODUCT SPECIFICATIONS

PRODUCT COMPOSITION	DATA
Material	100% pure Oxy-B1 vinyl
Additives	Oxy-B1 (Fungus Inhibitor), ultraviolet stabilizers
PRODUCT DIMENSIONS	
Thickness	9/16"
Standard Sizes	12" x 12" tiles, 3' x 4' or 3' x 12' pre-assembled panels
Case Pack	50 tiles per case
Weight	14.5 oz/tile
Colors	Burgundy, yellow, blue, almond, gray, black, hunter green, red, teal
PHYSICAL PROPERTIES	
Tensile Strength (ASTM D412)	2750 psi
Load Bearing Capacity	20 lbs per square centimeter
Elongation	96% retention of elongation, 107% retention of 100% modulus, 98% retention of tensile strength, 99% retention of color (weatherometer @ 720 hours)
Temperature Range (ASTM D746)	Designed for continuous environments from -30°F and not to exceed 167°F
Dielectic Strength (ASTM D149)	500volts/mil non-conductive
Insulation Resistance	1,000 mega ohms/1,000 ft. (UL 82-106)

COMMON USES

- Pools
- Health Clubs
- Locker Rooms
- Shower Areas
- Hot Tubs
- Saunas
- Ski Lodges
- Kitchens
- Restrooms

CLEANING & INSTALLATION

Installation

- Size up the area you wish to cover. Lay out the tiles with tabs pointing in the same directions.
- Snap the pins into the tabs. Repeat the process row by row, wall to wall.
- For large installations, tap pins into tabs with a hammer, trim your assembled surface for a precise fit.

Cleaning & Maintenance

- To clean the surface, brush it down with soapy water and rinse.
- To clean underneath, roll back and sweep or hose down.

*For more detailed procedures contact our trained Product Specialist or visit our website at www.matsinc.com

WARRANTY

Limited 1-Year Warranty. Mats, Inc. guarantees its Anti-fatigue tiles against deterioration due to faulty materials or workmanship. This guarantee does not cover damage that could occur from other abuses beyond the general intended application of the product. No other warranty is expressed or implied. Limit of liability from any losses resulting from the use of this product shall be for the purchase price only, and applied in form of credit, excluding any freight charges.