

**DESCRIPTION**

Total thickness	EN 428	mm	2.00
Weight	EN 430	g/m <sup>2</sup>	3300
Width of sheet	EN 426	cm	200
Length of sheet	EN 426	ml	20
Tile size	EN 427	mm	
Number of tiles per package	-	-	






**CLASSIFICATION**

Standard / Product specification		-	EN 649
European classification	EN 685	class	34 - 43
K rating	-	class	K5
Fire rating	EN 13501-1	class	B <sub>fl</sub> -s1
Critical radiant flux	ASTM E 648	class	
Marine Equipment Directive International Maritime Organisation	Directive 96/98/EC I.M.O code F.T.P.	n°	WARRINGTON 164.112/1121/WCL MED0179TE
Electrical resistance	EN 1081	Ohm	10 <sup>6</sup> ≤ R ≤ 10 <sup>8</sup>
	IEC 61340-5-1	Ohm	10 <sup>6</sup> ≤ R ≤ 10 <sup>9</sup>
	ANSI / ESD- S7.1	Ohm	10 <sup>6</sup> ≤ R ≤ 10 <sup>8</sup>
Static electrical propensity	EN 1815	kV	< 2
	IEC 61340-4-5	V	< 100

**PERFORMANCE**

Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 7.5
Wear group	EN 649	-	M
Dimensional stability	EN 434	%	≤ 0,40
Residual indentation	EN 433	mm	~ 0,03
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	-	OK
Anti-bacterial and fungicidal treatment	-	-	OK

**MARQUAGE CE**

	EN 14041	-	  
		-	 B <sub>fl</sub> -s1