




## **DIGITAL**SPECK<sub>"</sub>L I G H T I N G


digitalspeck.com


FIXTURE NO.: W-100 PUK SERIES			TYPE:	
DRAWN BY: DsS	DATE DRAWN:	9/24/12	1:4	
REVISED BY: PTO	DATE REVISED:	10/03/12	RFV· B	














## **HOUSING OPTIONS**

\_ DATE: \_

## **SPECIFICATIONS**

APPROVED: \_

OI LOI	ICATIONS		
DESIGN MODIFICATION RIGHTS RESERVED © 2012 DIGITAL SPECK LIGHTING by Manning			
HOUSING:	CONSISTS OF 0.090 THICK FABRICATED, LASER CUT ALUMINUM, WITH AN ELECTRO-GALVANIZED STEEL MOUNTING PLATE.		
	SPECIFY HOUSING DESIGN OPTION: W-100 W-102 W-104 W-106		
DRIVER:	2L8M35 - (2) INTEGRATED LED MODULES = 16 WATTS, 970 Lm, 3500K, 85 CRI, L70-60,000 HR.  UNIVERSAL VOLTAGE AND 0-10 DIMMING ARE AVAILABLE ON MOST SOLID STATE CONFIGURATIONS.  PLEASE CONSULT FACTORY WITH YOUR SPECIFIC CONTROL SYSTEM FOR VERIFICATION OF COMPATIBILITY.  "PP" POWDER PAINT - ALL SURFACES SEALED WITH A LOW VOC, THERMO CURE, POLYESTER POWDER COAT PAINT.  SEE WEB SITE OR CONTACT LOCAL AGENT FOR COLOR OPTIONS.		
	FIXTURE MOUNTS TO A STANDARD OCTAGONAL JUNCTION BOX. ALL MOUNTING HARDWARE TO BE SUPPLIED BY OTHERS. FIXTURE IS SUITABLE FOR USE IN "DAMP" LOCATIONS, WITH IP-65 RATED, UL RECOGNIZED COMPONENTS. TERRALUX: 5 YEARS.		