

Manual and Metering Faucets

Product Type

Deck Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet

Features & Specifications

- 8" Fixed Centers
- 8" Rigid / Swing Gooseneck Spout
- 1.5 GPM (5.7 L/min) Aerator
- 2-3/8" Lever Handle
- Quaturn Compression Operating Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser
- ECAST® design provides durable brass construction with total lead content equal to or less than 0.25% by weighted average

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- California Health and Safety Code 116875 (AB1953-2006)
- Vermont Bill S.152
- NSF/ANSI 372 Low Lead Content
- ADA ANSI/ICC A117.1
- CALGreen

Job Name \_\_\_\_\_

Item Number \_\_\_\_\_

Section/Tag \_\_\_\_\_

Model Specified \_\_\_\_\_

Architect \_\_\_\_\_

Engineer \_\_\_\_\_

Contractor \_\_\_\_\_

☐ Submitted as Shown      ☐ Submitted with Variations

Date \_\_\_\_\_



ECAST™

ECAST products are intended for installation where state laws and local codes mandate lead content levels or in any location where lead content is a concern.

## Architect/Engineer Specification

Technical drawing of a three-spout kitchen faucet. The drawing includes two side views and a top-down view of the faucet body. Dimensions are provided in inches and millimeters.

**Dimensions:**

- Overall width: 8 [203]
- Spout height: 13-1/8 [333]
- Spout reach: 8 [203]
- Spout diameter:  $\phi 2-1/4$  [57]
- Spout angle: 3°
- Spout base diameter:  $\phi 1-1/4$  [32]
- Spout base height: 2-3/8 [60]
- Spout base width: 4 [102]
- Spout base height: 7-1/2 [191]
- Spout base diameter:  $\phi 2-1/4$  [57]
- Spout base height: 1-3/8 [35] (MAXIMUM WARE THICKNESS)
- Spout base diameter:  $\phi 1-1/8$  [29]
- Spout base height: 4 [102]
- Spout base diameter:  $\phi 1-1/4$  [32]
- Spout base height: 2-3/8 [60]

**Notes:**

- 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER

Last Revision: 07/25/2011 • Date Printed: 03/25/2013 • Product specifications subject to change without notice