

Manual and Metering Faucets

Product Type

Deck Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet

Features & Specifications

- 8" Fixed Centers
- 8" Rigid / Swing Gooseneck Spout
- 2.2 GPM (8.3 L/min) Aerator
- 2-3/8" Lever Handle
- Quaturn Compression Operating Cartridge
- 1/2" NPSM Supply Inlets and Coupling Nut for 3/8" or 1/2" Flexible Riser

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown

☐ Submitted with Variations

Date _____



Architect/Engineer Specification

Technical drawing of a 1/2 inch NPSM coupling nut for 3/8 inch or 1/2 inch flexible riser. The drawing includes the following dimensions and labels:

- Overall Height:** 8 [203]
- Riser Diameter:** $\varnothing 2-1/4$ [57]
- Coupling Nut Diameter:** $\varnothing 1-1/8$ [29]
- Handle Length:** 2-3/8 [60]
- Handle Diameter:** $\varnothing 1-1/4$ [32]
- Base Diameter:** 4 [102]
- Top View Dimensions:**
 - Overall Width: 8 [203]
 - Radius: 8 [203]
 - Angle: 3°
 - Maximum Ware Thickness: 1-3/8 [35]
 - Base Diameter: 4 [102]
- Label:** 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER

Last Revision: 07/25/2011 • Date Printed: 03/25/2013 • Product specifications subject to change without notice