

MECHANICAL FAUCETS

201-RSGN8AE3VPXKCP



Manual and Metering Faucets

Product Type

Deck Mounted 8" Fixed Centers Concealed Hot and Cold Water Sink Faucet

Features & Specifications

- 8" Fixed Centers
- 8" Restricted Swing Gooseneck Spout
- 2.2 GPM (8.3 L/min) Vandal Proof Aerator
- 2-3/8" Vandal Proof Lever Handle
- Ceramic 1/4 Turn Operating Cartridge

Performance Specification

- Rated Operating Pressure: 20-125 PSI
- Rated Operating Temperature: 40-140°F

Warranty

- Lifetime Limited Faucet Warranty
- 5-Year Limited Cartridge Warranty
- 1-Year Limited Finish Warranty

Codes & Standards

- ASME A112.18.1/CSA B125.1
- Certified to NSF/ANSI 61, Section 9 by CSA
- ADA ANSI/ICC A117.1

Job Name _____

Item Number _____

Section/Tag _____

Model Specified _____

Architect _____

Engineer _____

Contractor _____

☐ Submitted as Shown ☐ Submitted with Variations

Date _____



2100 South Clearwater Drive
Des Plaines, IL
P: 847/803-5000
F: 847/803-5454
Technical: 800/TEC-TRUE
www.chicagofaucets.com

Architect/Engineer Specification

Technical drawing of a three-arm chandelier, showing two views: a side view (left) and a top view (right).

Side View Dimensions:

- Arm length (from base to light fixture): 2-3/8" [60]
- Base diameter: Ø 1-1/4" [32]
- Light fixture diameter: Ø 2-1/4" [57]
- Base to light fixture height: 4" [102]
- Base to light fixture height (total): 8" [203]
- Light fixture to base height: 1-1/8" [29]
- Light fixture to base height (total): 1-3/8" [35] (MAXIMUM WARE THICKNESS)

Top View Dimensions:

- Arm length (from base to light fixture): 8" [203]
- Light fixture diameter: Ø 2-1/4" [57]
- Base to light fixture height: 7-1/4" [184]
- Base to light fixture height (total): 13" [330]
- Light fixture to base height: 4" [102]
- Light fixture to base height (total): 1-3/8" [35] (MAXIMUM WARE THICKNESS)

Notes:

- 1/2 NPSM COUPLING NUT FOR 3/8 OR 1/2 FLEXIBLE RISER

Last Revision: 12/14/2011 • Date Printed: 03/25/2013 • Product specifications subject to change without notice