

FEATURES

- Gentle aerated warm water rinse
- Heated seat with temperature control
- Self-cleaning dual-action spray
- SoftClose® seat

MODELS

- SW502
Elongated only

COLORS/FINISHES

- Standard
#01 Cotton
#12 Sedona Beige



PRODUCT SPECIFICATION

Seat shall be model # SW502_____. Seat shall have gentle aerated warm water rinse with a self-cleaning dual-action spray. Seat shall be heated with temperature control panel. Seat shall be solid anti-bacterial plastic with closed front seat and cover. Seat shall include power cord, and water supply hoses.

CODES/STANDARDS

- Meets and exceeds ASME A112.4.2, ASME A112.18.1/CSA B125.1, UL 1431, CSA C22.2 #68
- Certifications: IAPMO(cUPC), State of Massachusetts, City of Los Angeles and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others



SPECIFICATIONS

- Power Rating: 120V AC, 60Hz, 313W
- Power Cord: Maximum length: 3.9 ft/120 cm, 3 prong grounded plug
- Water Feature: Adjustable Water Flow Rate:
Front washing - from 9.1 - 19.6 oz/min.
Back washing - from 9.8 - 20.3 oz/min.
- Washing Spray Temp: Minimum: 95°F/35°C
Maximum: 104°F/40°C
- Water Heater Capacity: 248W
- Water Heater Tank Volume: 0.20 gal./0.78L
- Safety Device: Thermal fuse, bimetal switch (overheating, auto reset), float switch (empty tank)
- Back Flow Prevention: Integral backflow protection complies with requirements in ASSE 1001 as required by ASME A112.4.2 and ASME A112.18.1/CSA B125.1
- Seat Warming Feature: Surface Temperature:
Minimum: 86°F/30°C
Maximum: 100°F/38°C (W/ Auto Energy Saver 79°F/26°C)
- Seat Heater Capacity: 50W
- Safety Device: Thermal fuse
- Water Supply Pressure: Minimum: 7 psi
Maximum: 110 psi
- Ambient Temperature: Range:
33°F/1°C to 95°F/35°C
- Weight: Net: 10.6 lbs/4.8 kg
Gross: (w/pkg) 17.4lbs/7.9kg
- Product Dimensions: 18-7/8" W x 20.5" D x 6-3/4" H
- Warranty: One Year Limited Warranty
- Shipping weight: 10.6lbs.
- Shipping dimensions: 23" x 20" x 9"

INSTALLATION NOTES

- Washlet B100 may not fit certain toilet bowl designs.
- If possible, with your order, please include your model number (from the underside of the tank lid).

