



## Material Safety Data Sheet

### Section 1 Chemical Identification

Importer: Marazzi USA  
359 Clay Road  
Sunnyvale, Texas 75182

Date: March 12, 2013

Product: Glass Tile Mosaics

Point of Contact: Steven T. Wiederwax  
Safety and Environmental Manager  
972-226-0110

### Section 2 Hazardous Ingredients

Ingredient	Percentage	PEL	TLV	Comments	Carcinogen
Crystalline Silica*	10 – 15%	30 mg/m <sup>3</sup> 0.1 mg/m <sup>3</sup>	0.1 mg/m <sup>3</sup>	Total Dust Respirable Dust	Yes

\* Crystalline Silica is a known carcinogen to the State of California.

Note: Crystalline Silica is inherent in the materials used to produce glass and the glass may contain trace amounts (< 0.1%) of cadmium, zinc, or chromium compounds.

### Section 3 Physical Data

Boiling Point (F): N/A	Percent Volatile by Volume: N/A
Vapor Pressure: N/A	Evaporation Rate: N/A
Solubility in Water: Insoluble	pH: N/A
Specific Gravity: N/A	Flashpoint: N/A
Appearance and Odor: Surface color varies with the individual pieces that comprise the tile with no distinguishable odor.	

<b>Section 4</b> <b>Fire and Explosion Data</b>
--

Flashpoint:	N/A	Lower Explosion Limit:	N/A
Flammability Class:	Non combustible	Upper Explosion Limit:	N/A
Extinguishing Media:	Water		

Fire Fighting Procedures: No special procedures are required. As in all fires, fire fighters should wear SCBA and full protective clothing.

Unusual Fire and Explosion Hazards: This product will not burn. Use appropriate techniques to fight surrounding fire.

<b>Section 5</b> <b>Health Hazard Information</b>
--

Routes of Exposure: Inhalation and Absorption

Acute Effects: Some skin irritation may occur from contact with any dust that results from cutting individual pieces of tile.

Chronic Effects: Crystalline silica is a known carcinogen and may produce a condition known as silicosis in humans.

First Aid Procedures:

- Eyes: Rinse eyes with clean water for at least 15 minutes. If irritation persists seek medical attention.
- Skin: Wash hands thoroughly with soap and water after handling.
- Inhalation: If a cough develops the individual should seek medical attention.

Personal Protective Equipment Requirements

- Skin: Water proof or water resistant gloves should be worn when installing tile.
- Eye: Protective glasses should be worn when cutting porcelain tile.
- Respiratory: A dust mask should be worn when dry cutting tile. If work activities will cause a dust cloud then a N95 or N100 rated respirator should be worn.

<b>Section 6</b> <b>Reactivity Data</b>
--

Stability: This is a stable material  
Hazardous Polymerization: Will not occur  
Incompatibilities: None known

Instability Conditions: None known  
Decomposition Temperature: Not Established  
Decomposition Products: None known

<b>Section 7</b> <b>Spill or Leak Procedures</b>
---

Spill or Leak Procedures: Not applicable

Waste Disposal Methods: Scrap tile should be disposed of in accordance with applicable state and local regulations. Scrap tile is not a hazardous waste under U.S. E.P.A. regulations.