shaw contract group®

tile specifications

style name	unleash tile	
style number	5T050	
construction	multi-level pattern loop	
fiber	eco solution q® nylon	
dye method	87% solution dyed/13% yarn dyed	
	english	metric
	-	
pattern repeat	none	
tufted weight	18.0	610.30 g/m ²
gauge	1/12	47.24 per 10 cm
stitches per inch	9.5	37.40 per 10 cm
finished pile thickness	0.115	2.92 mm
total thickness	0.247	6.27 mm
average density	5635	10.49 kilotex
product size	18" x 36"	45.72 cm x 91.44 cm
primary backing	synthetic	
secondary backing	ecoworx® tile	
protective treatments	ssp® shaw soil protection	CCA
gsa approved product	yes	GOM

testing


radiant panel nbs smoke electrostatic propensity

Class I less than 450 less than 3.5 kv

warranties

lifetime commercial limited

installation method









brick



coordinating products

melt tile, ignite tile, still tile

environmental certification

nsf140 platinum cradle to cradle silver certified





Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.

shawcontractgroup.com | 1 800.257.7429

shaw contract group" roll over each term to see a definition

unleash tile

eco impacts

end of life		
recyclability	100% recyclable	
shaw closed looped recycling	100.0% free pick up & recycling	
environmental guarantee		
To recycle call 800.509.SHAW		
materials		
ingredients		
face fiber	nylon 6	
dye method	87% solution dyed/13% yarn dyed	
backing	polyolefin composite	
surface treatments	non c8 flourocarbon chemistry	
does not contain PVC, phthalates, or PBD/PBDE		
recycled content		
total recycled content (by weight)	44.4 %	
pre-consumer	33.0 %	

post-consumer bio-based/rapidly renewable content (by weight) packaging country of origin (manufacturer)

114% 0.0 % 100% recyclable USA

Meets or exceeds all local and national regulations in country of manufacture. Manufactured in an ISO9001 & ISO14001 certified facility or equivalent. Recycled content is calculated using system allocation, mass balance, and direct insertion. The actual recycled content in this product will likely vary. For more information email info@shawgreenedge.com.

third party certifications

MBDC cradle to cradle silver certified **NSF 140** platinum certified CRI green label plus certified alp9968 **USGBC LEED** contributes **Building Research Establishment** certified Good Environmental Choice Australia certified certified 039-003 Singapore green label

social responsibility

Shaw and our people provide financial support, volunteer service and leadership for charitable and civic organizations in the communities where we work and live. Additionally, we strive to adhere to all applicable laws regarding labor, discrimination and harassment, wages and benefits, health and safety, diversity and equal opportunity.