

TECTUM ACOUSTICAL CEILINGS

Tectum ceiling panels combine a unique textured beauty with superior abuse resistance. These high-impact wood fiber panels combine several functions that truly set them apart for use in commercial, institutional, recreational and industrial buildings.

The panels are available in a wide range of sizes. They can be cut easily and shaped with standard woodworking tools, and installed in standard grid systems or direct attached. By using lay-in, Tonico, Multiplane, V-line and Designer Series Tectum panels, the designer can create a variety of three-dimensional patterns.

Tectum ceiling panels can be used in their attractive unpainted natural color, painted white, or custom colors. Also, these panels may be painted or re-painted in the field up to six times without reducing their acoustical properties.

Tectum decorative and acoustical panels can take repeated abuse and still retain their appearance. Tectum ceiling panels have remained the product of choice for over 50 years for any area where noise is a problem and the ceilings are subject to abuse.

Tectum ceiling panels meet the requirements of ASTM E-1264 Type XIV pattern L Class A.

NOTE: There is no asbestos, nor has there ever been any asbestos, used in Tectum products.





FEATURES:

- Reduces noise-NRC up to 1.00
- Class A/Class I interior finish
- Durability–tough, abuse resistant
- Flexible—easy to use
- Economical-longer life span
- Can be field painted six times (See Marketing Bulletin M-77 on our website for specific applications.)
- Nationwide distribution
- Proven performance-over 50 years
- R-Value is 1.75/inch
- Light reflectance up to .75





P.O. Box 3002 NEWARK, OH 43058

105 S. 6тн Sт. NEWARK, OH 43055



TECTUM ACOUSTICAL PERFORMANCE

TECTUM CEILING TILE

SOUND ARSORPTION COFFFICIENTS	102	IND A	RSOR	PTION	COFFFICI	FNITS
-------------------------------	-----	-------	------	-------	----------	-------

Panel Type	125	250	500	1000	2000	4000	NRC	Mounting
1" x 24" x 24" Lay-in	.40	.43	.35	.48	.60	.93	.45	E-400
1 ¹ / ₂ " x 24" x 24" Lay-in	.44	.43	.33	.49	.66	.77	.50	E-400
2" x 24" x 24" Lay-in	.48	.46	.36	.55	.74	.79	.55	E-400
1" x 24" x 24"								
Tonico / Soft Tonico	.37	.43	.34	.45	.58	.94	.45	E-400
1 ¹ / ₂ " x 24" x 24" Designer	.44	.47	.36	.51	.71	1.06	.50	E-400
1 ¹ / ₂ " x 24" x 24"								
Designer Plus	.35	.42	.39	.51	.72	1.05	.50	E-400
2" C-2 24" x 24"	.43	.50	.42	.62	.86	1.04	.60	E-400
3" C-3 24" x 24"	.70	.50	.52	.76	.92	1.16	.70	E-400
1" x 24" x 24" Lay-in								
panel with 61/4"								
Fiberglass Backing	1.01	.89	1.06	.97	.93	1.13	.95	E-400
1" x 24 x 24" Tonico /								
Soft Tonico with								
6 ¹ / ₄ " Fiberglass Backing	1.14	1.01	1.06	.94	.93	1.12	1.00	E-400
1" x 24" x 24" Lay-in								
panel with								
3 ⁵ / ₈ " Fiberglass Backing	.85	.81	.84	.82	.83	1.01	.85	E-400
1 ¹ / ₂ " Clouds	.44	.43	.33	.49	.66	.77	.50	E-400
1 ¹ / ₂ " Clouds with								
6" Fiberglass Backing	1.01	.89	1.06	.97	.93	1.13	.95	E-400
HANGING BAFFLES								
1' Face to Face (1" Thick)	1.62	1.35	2.36	3.81	4.76	6.54		
2' Face to Face (1" Thick)	.95	1.63	2.32	3.92	5.18	7.27		
3' Face to Face (1" Thick)	1.01	1.44	2.32	4.05	5.16	7.21		
VARIATIONS LAY-IN C	FILING TILE							

VARIATIONS LAY-IN CEILING TILE

1" Variations (Lay-In) .47 .53 .35 .50 .68 .86 .57 E-400

i variations (Lay-III)	.47	.55	.00	.50	.00	.00	.51				00
TECTUM PROD		Actual	Educ	Factoms	Links	Flame		10	ما سام		
Panel Type	Nominal Thickness (inches)	Size (inches)	Edge Detail	Factory Finish	Light Reflectance	Spread			eigh 3S/SI		
							1"	1 ¹ /2"	2"	2 ¹ / ₂ "	3"
Standard Tectum Tile	1, 1 ¹ / ₂ , 2 1 ¹ / ₂	23 ³ / ₄ x 23 ³ / ₄ , 47 ³ / ₄ 47 ³ / ₄ x 47 ³ / ₄	Square	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53 2.5	3.3		
Full-Span Corridor Panels	1, 1 ¹ / ₂ , 2	23 ³ / ₄ or 29 ³ / ₄ x 48 up to 144	Face Rabbeted Two Long Sides	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53	3.3		
Acousti-Tough Ceiling System™	1, 1 ¹ / ₂ , 2	23 ³ / ₄ x 23 ³ / ₄ 23 ³ / ₄ x 47 ³ / ₄	Square	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53	3.3		
Tonico	1 1 ¹ / ₂	23 ³ / ₄ x 23 ³ / ₄ , 47 ³ / ₄ 23 ³ / ₄ x 23 ³ / ₄ , 47 ³ / ₄ , 47 ³ / ₄ x 47 ³ / ₄	Face Rabbeted	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53			
Designer Series	1, 1 ¹ / ₂	23 ³ / ₄ x 23 ³ / ₄ 23 ³ / ₄ x 47 ³ / ₄ 23 ³ / ₄ x 95 ³ / ₄	Face Rabbeted	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53			
Designer Series Plus	1, 1 ¹ / ₂	23 ³ / ₄ x 23 ³ / ₄	Face Rabbeted	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53			
Security Ceiling Panel	1, $1^{1/2}$, & 2 plus 24 ga. steel plate $1^{1/2}$, & 2 plus 24 ga. steel plate	23 ³ / ₄ x up to 96 23 ³ / ₄ x up to 96	Beveled Tongue & Groove	White, Natural, Custom Colors	.75 / .60	0-25	4.0	4.8			
Multi-Plane	1, 2, 2 ¹ / ₂ , 3	23 ³ / ₄ x 23 ³ / ₄	Face Rabbeted	White, Natural, Custom Colors	.75 / .60	0-25	1.63		3.3	4.3	5.3
Soft Look Tonico	1	23 ³ / ₄ x 23 ³ / ₄ , 47 ³ / ₄ 47 ³ / ₄ x 47 ³ / ₄	Face Rabbeted	White, Natural, Custom Colors	.75 / .60	0-25	1.63 2.53				
Concealed Corridor Ceiling Panels	1 ¹ / ₂ , 2	23 ³ / ₄ x up to 144	Beveled Rabbeted One Side Beveled Kerfed, Rabbeted	White, Natural, Custom Colors	.75 / .60	0-25	2.53		3.3		
Hanging Baffles	1, 1 ¹ / ₂ , 2	11 ³ / ₄ , 23 ³ / ₄ x 48	Bottom Edges Beveled Both Sides	White, Natural, Custom Colors	.75 / .60	0-25	1.63	2.53	3.3		
Clouds	1 ¹ / ₂ , 2	23 ³ / ₄ , 47 ³ / ₄ up to 144 23 ³ / ₄ x up to 96, 47 ³ / ₄ x 47 ³ / ₄	, Square and Radius	White, Natural, Custom Colors	.75 / .60	0-25		2.53	3.3		

Pub. #T101

www.tectum.com e-mail: info@tectum.com Phone: 888-977-9691 Fax: 800-832-8869