IVY FRAMEWORK

262-003





Seating/Panel





CONTENT

100% Pre-Consumer Recycled Polyester

BACKING

None

FINISH None

APPROVED FOR

Nano-Tex, DuraBlock

WIDTH

WEIGHT

DIR

SHOWN RR

54"

10.5 oz./linear yard

Yes

VISUAL REPEAT

3.5" H, 4.25" V

ROLL LENGTH

58 yards

BREAKING STRENGTH

Warp 275 min/Fill 200 min

ABRASION RESISTANCE

Passes 60,000 Double Rubs

PILLING RESISTANCE

Class 4 min

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 3 mi

COLORFASTNESS TO LIGHT

40 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

FLAMMABILITY

Passes Cal 117 Section E; NFPA 260 (Equiv. to UFAC) Class 1. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.





