

RED PATENT

PA-001



CATEGORY

Seating/Panel

PROPERTIES



CONTENT

100% Polyurethane - PVC FREE

BACKING

100% Polyester

FINISH

None

WIDTH

54"

WEIGHT

25 oz./linear yard

DIR

No

SHOWN RR

No

VISUAL REPEAT

None

ROLL LENGTH

30 yards

BREAKING STRENGTH

Warp 170/Fill 90

ABRASION RESISTANCE

Passes 500,000 Double Rubs

PILLING RESISTANCE

Class n/a

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 mi

COLORFASTNESS TO LIGHT

200 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

BC: Bleach Cleanable - 1 part bleach, 10 parts water = 9% bleach, 91% water solution. Always rinse promptly with clean water after applying the bleach solution.

FLAMMABILITY

Passes Cal 117 Section E; NFPA 260 (Equiv. to UFAC) Class 1; ASTM E84 Class 1 or A; IMO A.652(16) 8.2 & 8.3. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

Notes:

Horizontal lines for notes.

GREENGUARD
Certified



GS-28F-0022P

Copyright Mayer Fabrics 2014

Specifications are subject to change
Current specifications are available at mayerfabrics.com

321 South Alabama Street, Indianapolis, IN 46204 T: 317.267.2626 F: 317.267.2629 Since 1897