

SADDLE MAVERICK

MK-010



CATEGORY
Seating

PROPERTIES

CONTENT
100% Vinyl

BACKING
100% Polyester Knit

FINISH
Resilience^{SR}

| | | | |
|---------------------|-------------------------------------|------------------|-----------------------|
| WIDTH 54" | WEIGHT 28 oz./linear yard | DIR No | SHOWN RR No |
|---------------------|-------------------------------------|------------------|-----------------------|

| | |
|------------------------------|--------------------------------|
| VISUAL REPEAT None | ROLL LENGTH 30 yards |
|------------------------------|--------------------------------|

BREAKING STRENGTH
Warp 95/Fill 60

ABRASION RESISTANCE
Exceeds 250,000 Double Rubs

PILLING RESISTANCE
Class

COLORFASTNESS TO CROCKING
Dry: Class 4 min/Wet: Class 4 mi

COLORFASTNESS TO LIGHT
650 hours - Suitable for marine use

CLEANING
WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.
BC: Bleach Cleanable - 1 part bleach, 9 parts water = 10% bleach, 90% water solution. Always rinse promptly with clean water after applying the bleach solution.

FLAMMABILITY
Passes Cal 117-2013; NFPA 260 (Equiv. to UFAC) Class 1; BIFMA; FMVSS 302; IMO FTP 2010 Code MSC.307(88), Part 8, 3.1 & 3.2; May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

Notes:

Resilience^{SR}
ENDURING PROTECTION

GREENGUARD
Certified

GSA
GS-28F-0022P