

OATMEAL DURAWEAVE

361-007



MAYERFABRICS



CATEGORY

Seating

PROPERTIES



CONTENT

100% Solution Dyed Olefin

BACKING

Latex

FINISH

Stain Repellent

APPROVED FOR

Nano-Tex, DuraBlock

WIDTH

54"

WEIGHT

18 oz./linear yard

DIR

Yes

SHOWN RR

No

VISUAL REPEAT

None

ROLL LENGTH

50 yards

BREAKING STRENGTH

Warp 275/Fill 280

ABRASION RESISTANCE

10 Yr Warranty - Exceeds ACT Requirement

PILLING RESISTANCE

Class 5

COLORFASTNESS TO CROCKING

Dry: Class 4 min/Wet: Class 4 mi

COLORFASTNESS TO LIGHT

400 hours

CLEANING

WS: Water/Solvent Cleaner - Spot clean with a mild solvent, an upholstery shampoo, or the foam from a mild detergent. When using a solvent or dry cleaning product, follow instructions carefully and clean only in a well-ventilated room. Avoid any product that contains carbon tetrachloride or other toxic materials. With either method, pretest a small area before proceeding. Always rinse promptly with clean water.

FLAMMABILITY

Passes Cal 117 Section E; NFPA 260 (Equiv. to UFAC) Class 1; ASTM E84 Class 1 or A. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

Notes:



Water and Stain
Repellent Finish



GS-28F-0022P

Copyright Mayer Fabrics 2014

Specifications are subject to change
Current specifications are available at mayerfabrics.com