

LAGOON DAKOTA

DK-034



CATEGORY
Seating

PROPERTIES

CONTENT
100% Vinyl

BACKING
Polyester

FINISH
PVC/Acrylic

WIDTH 54"	WEIGHT 32.25 oz./linear yard	DIR Yes	SHOWN RR No
---------------------	--	-------------------	-----------------------

VISUAL REPEAT None	ROLL LENGTH 30 yards
------------------------------	--------------------------------

BREAKING STRENGTH
Warp 109/Fill 80

ABRASION RESISTANCE
Exceeds 500,000 Double Rubs

PILLING RESISTANCE

COLORFASTNESS TO CROCKING
Dry: Class n/a /Wet: Class N/A


COLORFASTNESS TO LIGHT
150 hours

CLEANING
W: Water-Based Cleaner - Spot clean, using the foam only from a water-based cleaning agent, such as a mild detergent or non-solvent upholstery shampoo product. Apply foam with a soft brush in a circular motion. Always rinse promptly with clean water. Vacuum when dry. Pretest a small area before proceeding. In general, most common stains can be cleaned using warm, soapy water and clear water rinses. Moderate scrubbing with a medium bristle brush will help loosen soiling materials from the depressions of embossed surfaces.

FLAMMABILITY
Passes Cal 117-2013; Cal 117 Section E; NFPA 260 (Equiv. to UFAC) Class 1; FAA/FAR 25.853(a) & Appendix F Part I(a)(ii); Fed. Spec. CID A-A-2950/supersedes CCC-A-680A; FMVSS 302; NY & NJ Port Authority; Fed. Spec. CCC-A-700J; Fed. Std. 191A Test Method 5903.1; Fed. Spec. CCC-A-700J; Fed. Std. 191A Test Method 5903.1. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

Notes:

MorCare™
NOW MORE THAN EVER



321 South Alabama Street, Indianapolis, IN 46204 T: 317.267.2626 F: 317.267.2629 Since 1897