

FELDSPAR TUSSAH

TH-003



MAYERFABRICS



CATEGORY
Seating

PROPERTIES

CONTENT

100% Vinyl - PVC FREE

BACKING

Polyester

FINISH

PVC/Acrylic

WIDTH

54"

WEIGHT

32.25 oz./linear yard

DIR

Yes

SHOWN RR

Yes

VISUAL REPEAT

9.25" H, 4.38" V Random Match

ROLL LENGTH

30 yards

BREAKING STRENGTH

Warp 109/Fill 80

ABRASION RESISTANCE

Exceeds 500,000 Double Rubs

PILLING RESISTANCE

COLORFASTNESS TO CROCKING

Dry: Class n/a /Wet: Class N/A

COLORFASTNESS TO LIGHT

150 hours

CLEANING

W: Water-Based Cleaner - Spot clean, using the foam only from a water-based cleaning agent, such as a mild detergent or non-solvent upholstery shampoo product. Apply foam with a soft brush in a circular motion. Always rinse promptly with clean water. Vacuum when dry. Pretest a small area before proceeding. In general, most common stains can be cleaned using warm, soapy water and clear water rinses. Moderate scrubbing with a medium bristle brush will help loosen soiling materials from the depressions of embossed surfaces.

FLAMMABILITY

Passes Cal 117 Section E; NFPA 260 (Equiv. to UFAC) Class 1; FAA/FAR 25.853(a) & Appendix F Part I(a)(ii); Fed. Spec. CID A-A-2950/supersedes CCC-A-680A; FMVSS 302; NY & NJ Port Authority; Fed. Spec. CCC-A-700J; Fed. Std. 191A Test Method 5903.1; Fed. Spec. CCC-A-700J; Fed. Std. 191A Test Method 5903.1. May comply with Cal. Tech. Bul. 133 when combined with appropriate components.

Notes:

MorCare™

NOW MORE THAN EVER



GS-28F-0022P

Copyright Mayer Fabrics 2015

Specifications are subject to change
Current specifications are available at mayerfabrics.com

321 South Alabama Street, Indianapolis, IN 46204 T: 317.267.2626 F: 317.267.2629 Since 1897