

GLAZED PORCELAIN

ALESSI™



 **daltile**[®]
DESIGN WITH CONFIDENCE™

floor • wall • countertop

ALESSI™

GLAZED PORCELAIN

Field Tile



CREMA AL05



DORATO AL06



NOCE AL07

SIZES

		SQ. FT. CARTON	PIECES PER CARTON
20 x 20 Field Tile	(19-11/16" x 19-11/16") (50.0 cm x 50.0 cm)	21.52	8
13 x 13 Field Tile	(13-1/8" x 13-1/8") (33.0 cm x 33.0 cm)	14.10	12

RESIDENTIAL USAGE

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F	W	C		

COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios	✓	✓			
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops	✓	✓	✓	✓	✓
Pool Decking					
Pool Linings	✓	✓	✓	✓	✓

Suitable for exterior walls in freezing and non-freezing climates when proper installation methods are followed.

NOTES

Special care needs to be given when installing tiles 20" and larger. Please refer to www.daltileproducts.com/LargeTiles for information.

Use of a latex modified thin-set is recommended for installation.

Since there are variations in all fired ceramic products, the tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile and trim samples or color reproductions.

Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: www.daltile.com/CommercialFactors

Water, oil, grease etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection.

TRIM

	TYPE	NUMBER	SIZE	PIECES PER CARTON
	Bullnose	S-43E9	3 x 13	36

SHADE VARIATION

HIGH (V3)

Some variation from tile to tile, and within each tile

INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
5/16"	1/8"

SLIP RESISTANCE (WET) : 2

The higher the rating, the higher the slip resistance.

1	< .50
2	.50 - .59
3	≥ .60

TEST RESULTS

	ASTM#	RESULT
Water Absorption	C373	<0.5%
Breaking Strength	C648	>350 lbs.
Scratch Hardness	MOHS	8.0
Chemical Resistance	C650	Resistant
Coefficient of Friction	CI028	Wet: ≥0.50 Dry: ≥ 0.60
Abrasion Resistance	CI027	4

ALESSI™

GLAZED PORCELAIN



floor • wall • countertop



daltile
greenworks™
ENVIRONMENTAL LEADERSHIP THAT WORKS

By their very design, Daltile products can help make it easier for you to earn LEED™ points and/or points towards many industry leading green home building programs. From using recycled material content to establishing manufacturing facilities within 500 miles of your project, we help ensure you don't have to compromise your design to be environmentally conscious. For detailed information, visit daltilegreenworks.com.



TRU-EDGE

CERTIFIED
PORCELAIN™
TILE
0.5% or less water absorption



daltile®

7834 C. F. Hawn Freeway | Dallas, TX 75217 | 214.398.1411 800.933.TILE
For more information about Daltile products and services, visit our website at daltile.com

©2012 Dal-Tile Corporation (6/12) SSDTALESSI