

GLAZED PORCELAIN FLOOR – GLAZED CERAMIC WALL & MOSAIC *with* REVEAL IMAGING™  
**AVONDDALE™**



# AVONDALE™

GLAZED PORCELAIN FLOOR –  
GLAZED CERAMIC WALL & MOSAIC  
*with REVEAL IMAGING™*



## A TILE FOR ANY STYLE, A STYLE FOR ANY ROOM

Stunning in its depth and movement, Avondale from Daltile will transform any space. Neutral colors and softly illuminated tones emulate the warmth of natural limestone. Its deep color tones and moving graphics give it added dimension. Avondale's porcelain floor tile and complementary ceramic wall and mosaic tiles allow for a wealth of design options. Find gorgeous details within the surface as you explore the many facets of Avondale.

- **REALISTIC LOOK**
  - Realistic graphics and color demonstrate depth and movement to help create a classic visual appeal
  - Emulates a limestone visual with wide graphic variation in three color tones
- **COORDINATING FORMATS**
  - Coordinating floor, wall, and mosaic tiles offer more design possibilities
- **NEUTRAL COLORS**
  - Warm color palette easily integrates with any style or design

## FINISH THE LOOK

Create a custom look with these coordinating mosaics.

COORDINATING GLAZED CERAMIC MOSAICS



CHATEAU CRÈME AD01



WEST TOWER AD02



CASTLE ROCK AD03

Above photo features Castle Rock 10 x 14 wall tile with Glass Horizons Arctic Blend 3/4 x Random mosaic as a decorative accent.  
Cover photo features Chateau Crème 18 x 18 in a grid pattern on the floor. Walls feature 10 x 14 wall tile and 2 x 4 brick-joint mosaics.

# AVONDALE™

GLAZED PORCELAIN FLOOR –  
GLAZED CERAMIC WALL & MOSAIC  
*with* REVEAL IMAGING™

GLAZED PORCELAIN FLOOR TILE



CHATEAU CRÈME AD01



WEST TOWER AD02



CASTLE ROCK AD03


COORDINATING GLAZED CERAMIC WALL TILE



CHATEAU CRÈME AD01



WEST TOWER AD02



CASTLE ROCK AD03

# AVONDALE™

GLAZED PORCELAIN FLOOR –  
GLAZED CERAMIC WALL & MOSAIC  
with REVEAL IMAGING™



## SIZES

		SQ.FT. CARTON	PCS. PER CARTON
18 x 18 Field Tile	(17-3/4" x 17-3/4") (45.20 cm x 45.20 cm)	18.00	8
12 x 24 Field Tile	(11-11/16" x 23-5/8") (29.70 cm x 60.00 cm)	16.00	8
12 x 12 Field Tile	(11-13/16" x 11-13/16") (30.00 cm x 30.00 cm)	11.00	11
10 x 14 Wall Tile	(9-27/32" x 13-31/32") (25.00 cm x 35.50 cm)	14.55	15
2 x 4 Brick-joint Mosaic	(11-7/8" x 11-7/8" Sheet) (30.20 cm x 30.20 cm)	9.96	12

## RESIDENTIAL USAGE

FLOORS	WALLS	COUNTERTOPS	EXTERIOR PATIOS	EXTERIOR POOL DECKS
F*	W	C	EP	ED

Floor tile is suitable for residential exterior floors and walls in freezing and non-freezing climates when proper installation methods are followed.

Wall tile is suitable for residential exterior walls in non-freezing climates when proper installation methods are followed.

Mosaic tile is suitable for residential exterior floors and walls in non-freezing climates when proper installation methods are followed.

\* Wall tile is suitable to be used on interior bathroom floors where the floor is not subject to exterior foot traffic, when proper installation methods are followed.

## COMMERCIAL USAGE

	INTERIOR			EXTERIOR	
	RESIDENTIAL	LIGHT COMMERCIAL	COMMERCIAL	RESIDENTIAL	COMMERCIAL
Floors/Patios*	✓	✓	✓	✓	
Walls/Backsplashes	✓	✓	✓	✓	✓
Countertops	✓	✓	✓	✓	✓
Pool Decking					
Pool Linings	✓	✓	✓	✓	✓

Floor tile suitable for exterior floors (excluding pool decking) in freezing and non-freezing climates when proper installation methods are followed.

Mosaic tile suitable for exterior floors (excluding pool decking) in non-freezing climates when proper installation methods are followed.

Wall tile suitable for exterior walls in non-freezing climates when proper installation methods are followed.

\*Floor tile and mosaics only



## TRIM

TYPE	NUMBER	SIZE
Floor Bullnose*	P-43C9	3 x 12
Wall Bullnose	S-4310	3 x 10
Wall Bullnose Corner	SN-4310	3 x 3

\*Floor bullnose is intended to coordinate with floor field tile in the standard 90-degree installation position.

## SHADE VARIATION



## INSTALLATION

THICKNESS	GROUT JOINT RECOMMENDATION
Floor & Wall: 5/16" Mosaic: 1/4"	Floor: 3/16" Wall: 1/16" Mosaic: 1/8"

## TEST RESULTS

	ASTM#	Floor Result	Wall Result	Mosaic Result
Water Absorption	C373	< 0.5%	< 20.0%	< 3.0%
Breaking Strength	C648	> 275 lbs.	100-230 lbs	> 250 lbs
Scratch Hardness	MOHS	8.0	4.0-6.5	8.0
Chemical Resistance	C650	Resistant	Resistant	Resistant
Dynamic C.O.F.	A137.1	≥ 0.42	< 0.42	≥ 0.42
Abrasion Resistance	CI027	4	--	4

A DCOF value of ≥ 0.42 is the new standard for tiles specified for commercial application in standard A137.1–2012, Section 9.6. It replaces the SCOF value of ≥ 0.60 referenced in ASTM C1028. For more information on the correlation between the two values and about the DCOF AcuTest™ please visit: <http://daltil.com/information/DCOF>.

## NOTES

Use of a latex modified thin-set is recommended for installation.

Special consideration needs to be given when installing tiles 20" and larger. Please refer to [www.daltil.com/LargeTiles](http://www.daltil.com/LargeTiles) for more information.

Since there are variations in all fired ceramic products, tile and trim supplied for your particular installation may not match these samples. Final color selection should be made from actual tiles and trim and not from tile samples or color reproductions. Manufactured in accordance with ANSI A137.1 standards.

Water, oil, grease, etc. create slippery conditions. Floor applications with exposure to these conditions require extra caution in product selection. Not for use on ramps.

For additional information refer to "Factors to Consider" at: <http://daltil.com/CommercialFactors> or <http://daltil.com/ResidentialFactors>.



DESIGN WITH CONFIDENCE™

7834 C. F. Hawn Freeway | Dallas, Texas 75217 | 800.933.TILE

For more information about DalTile products and services, visit our website at [DALTILE.COM](http://DALTILE.COM).

© 2014 Dal-Tile Corporation (3/14)