VCT

Technical Data	Standards	VCT	Solids & Feature Strips
Type of Floor Covering		Vinyl Composition Tile	Vinyl Composition Tile
Classification	ASTM F 1066	Class 2 Through Pattern	Class 1 Solid Color
Total Thickness		1/8" (3.2 mm)	1/8" (3.2 mm)
Static Load Limit	ASTM F 970	150 psi	150 psi
Tile Size Weight/sq. ft./m² Carton Quantity Carton Weight		12" x 12" (305 mm x 305 mm) 1.4 lbs sq. ft. (14.0 lbs. m²) 45 tiles = 45 sq. ft. (4.18 m²) 64 lbs (29.0 kg)	12" x 12" (305 mm x 305 mm) 1.4 lbs sq. ft. (14.0 lbs. m²) 45 tiles = 45 sq. ft. (4.18 m²) 64 lbs (29.0 kg)
Flammability	ASTM E 648	Class 1 >0.45 CRF	Class 1 >0.45 CRF
Smoke Density	ASTM E 662	<450	<450
Slip Resistance SCOF	ADA Compliant		
Chemical Resistance		Good	Good
Colors		73 Standard Price	4 Premium Price Solids
Warranty		5 Year LIMITED Warranty. See tarkettna.com for complete warranty information.	5 Year LIMITED Warranty. See tarkettna.com for complete warranty information.
Maintenance		Conventional VCT Maintenance 3-5+ coats of finish*	Conventional VCT Maintenance 3-5+ coats of finish*

Feature Strips
Sizes, Quantities & Weights

1/4" x 24"
100 pieces per ctn -
200 lin. ft. (60.96 lin. m per ctn)
6 lbs per ctn (2.7 kg)

1/2" x 24"
75 pieces per ctn -
150 lin. ft. (45.72 lin. m per ctn)
9 lbs per ctn (4 kg)

1" x 24"
50 pieces per ctn -
100 lin. ft. (30.48 lin. m per ctn)
11.5 lbs per ctn (5.2 kg)

2" x 24"
25 pieces per ctn -
50 lin. ft. (15.24 lin. m per ctn)
12 lbs per ctn (5.4 kg)

4" x 24"
15 pieces per ctn -
30 lin. ft. (9.14 lin. m per ctn)
14 lbs per ctn (6.3 kg)

6" x 24"
15 pieces per ctn -
30 lin. ft. (9.14 lin. m per ctn)
21 lbs per ctn (9.5 kg)

* Depending upon use of the floor.
Please visit tarkettna.com for the most updated specifications, and installation, cleaning and maintenance instructions.
The Johnsonite system includes transitions and finishing borders (wall base) to complete your flooring design and installation.

How to Order: **VCT Standard** V-(XXX) Color Number or
V-(XXXX) Color Number   **VCT Solids** VS(XXX) Color Number

- *Phthalate free**
- *85% natural limestone -abundant in nature*
  - *Contains both Pre&Post-Consumer recycled content*
- *Recycled VCT into VCT*
  except post-consumer recycled content

good materials

- *Since 2011, achieved 5% yearly reduction goals in water, waste, energy and green gas emissions*
- *Made in the U.S.A.*

resource stewardship

Sustainability Tarkett

reuse and recycle

- *ReStart® program reclaims samples, installation waste and flooring at end of use*

people friendly spaces

- *FloorScore™ certified meeting CA01350*
- *TVOCs under 10 µg/cubic meter (under limit of quantification)*
- *NSF-332 Gold*
- *Low-emitting water-based adhesives*

16910 Munn Road
Chagrin Falls, OH 44023
800-899-8916 or 440-543-8916

tarkettna.com

Tarkett
THE ULTIMATE FLOORING EXPERIENCE

SPEED SWATCH
800-899-8916

©2014 Tarkett
Printed in the USA 6/14